

For 89-10
(Rev. 1951)

APPROVED

JUL 27 1956

JERRY W. LONG
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4
Approval expires 12-31-60.

Land Office **Santa Fe**
Lease No. **079298-5**
Unit **San Juan 28-7 Unit**
14-08-001-459

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	Water Fracture	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 12, 1956

Well No. 63 is located 1845 ft. from N line and 1650 ft. from E line of sec. 12

S1 Section 12 27N 7W BNPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6612 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

June 30, 1956 T.D. 5664'. Cleanout Depth 5614'. Water fractured Lower Point Lookout perf. int. 5500-5510, 5520-5530 & 5555-5570 w/56,200 gals. water & 50,000# sand. BHP 1700#, max. pr. 1500#, avg. tr. pr. 1300#. Inj. rate 54 BPM. Flush 6000 gals.

June 30, 1956 T.D. 5664'. Temporary B.P. @ 5460'. Water fractured Upper Point Lookout perf. int. 5400-5412 & 5420-5432 w/49,600 gals. water & 39,000# sand. BDP 2000#, max. pr. 3500#, avg. tr. pr. 2300#. Inj. rate 58.5 BPM. Flush none.

7-2-56 T.D. 5664'. Temp. B.P. @ 5370'. Water fractured Cliff House perf. int. 4894-4906, 4918-4928, 4940-4950, 4964-4972, 4978-4988 w/51,813 gals. water & 60,000# sand. BHP 1900#, max. pr. 2250#, avg. tr. pr. 1800#. Inj. rate 48.0 BPM. Flush 4988 gals.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By R. W. [Signature]
Petroleum Engineer

Title _____

(SUBMIT IN TRIPLICATE)

Land Office Santa FeLease No. 77291-8Unit S. R. Juan 2-7 Unit
14-00-001-439UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	WATER PRODUCTION	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 12, 1956

Well No. 23 is located 144 ft. from N line and 1050 ft. from E line of sec. 12

Section 12 27N 7E 14PM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco El Paso New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5042 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

June 30, 1956 P.D. 5004'. Cement depth 5014'. Water fractured Lower Point Lookout part. int. 5500-5510, 5520-5530 & 5550-5570 w/50,200 gals. water & 50,000 gals. sand. IDP 1700%, max. pr. 1500%, av. tr. pr. 1300%. Inf. rate 54 BPM. Flush 6000 gals.

June 20, 1956 P.D. 5004'. Temporary P.D. @ 5400'. Water fractured Upper Point Lookout part. int. 5400-5412 & 5420-5432 w/49,000 gals. water & 19,000 gals. sand. IDP 2000%, max. pr. 3500%, av. tr. pr. 2300%. Inf. rate 5.5 BPM. Flush none.

7-2-56 P.D. 5004'. Temp. P.D. @ 5370'. Water fractured CLINT House part. int. 4940-4950, 4960-4970, 4980-4990, 4990-5000 w/51,000 gals. water & 60,000 gals. sand. IDP 1900%, max. pr. 2250%, av. tr. pr. 1800%. Inf. rate 45.0 BPM. Flush 4900 gals.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas CompanyAddress Box 221Marathon, New Mexico

By

[Signature]
 Petroleum Engineer
 Title