

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
JUL 5 1995
OIL COFF. DIV.

Sundry Notices and Reports on Wells

FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1650' FNL, 990' FEL, Sec. 8, T-27-N, R-6-W, NMPM

- 5. Lease Number
NM-03583
- 6. If Indian, All. or Tribe Name
- 7. Unit Agreement Name
San Juan 28-6 Unit
- 8. Well Name & Number
San Juan 28-6 U #22
- 9. API Well No.
30-039-07127
- 10. Field and Pool
Blanco Mesaverde
- 11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input checked="" type="checkbox"/> Other - Sidetrack workover

13. Describe Proposed or Completed Operations

Procedure change submitted by letter dated 2-2-95, approved by Steve Mason, BLM

- 5-9-95 MIRU. ND WH. NU BOP. PT BOP. TOO H w/80 jts 2 3/8" tbg. SDON.
- 5-10-95 TOO H w/74 jts 2 3/8" tbg. TIH w/7" csg scraper to 4773'. TOO H. TIH w/7" cmt retainer, set @ 4743'. Load tbg w/16 bbl wtr. PT tbg to 2000 psi, OK. Load 7" csg w/170 bbl wtr, circ hole clean. PT csg to 1000 psi, OK. Leave 500 psi on csg. Establish injection. Pump 275 sx Class "B" neat cmt below cmt retainer & 5 sx Class "B" cmt on top of cmt retainer. POOH to 4712'. Reverse circ w/30 bbl wtr. Reverse circ 1/2 bbl cmt to surface. POOH. SDON.
- 5-11-95 Load hole w/9 bbl wtr. TIH, ran CBL-CCL-VDL @ 0-4724' w/1000 psi on csg, TOC @ 290'. RD. ND BOP. NU WH. RD, Rig released.
- 6-11-95 MIRU. ND WH. NU BOP. TIH, PT BOP & csg to 1000 psi, OK. Drill cmt & cmt retainer @ 4743-4800'.
- 6-12-95 Drill cmt @ 4800-4820'. POOH. TIH w/downhole motor. Time drill @ 4820-4890'. POOH.
- 6-13-95 TIH w/bit. Ream hole @ 4835-4890'. Drill @ 4890-5279'.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 6/23/95

(This space for Federal or State Office use)
APPROVED BY _____ Title _____
CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

JUN 29 1995

FARMINGTON DISTRICT OFFICE
BY [Signature]

NMOCD

- 6-14-95 Drill from 5279' to TD @ 5895'. Circ hole clean. TOOH. Prepare to log.
- 6-15-95 Log well. RD. TIH w/135 jts 4 1/2" 10.5# K-55 csg, set @ 5864'. Pump 20 bbl gelled wtr, 10 bbl wtr. Cmtd w/80 sx 50/50 poz w/0.3% Halad-344, 0.25 pps Celloflake, 3 pps Gilsonite (105 cu.ft.). Tailed w/100 sx Class "B" cmt w/2% calcium chloride (118 cu.ft.). Displace.
- 6-16-95 TIH, drill cmt @ 5701-5818'. Circ hole w/1 1/2" Kcl wtr. WOC. Spot 500 gal 15% Hcl @ 5747'. POOH. RU, ran CBL-CCL-GR @ 3000-5810'. TOC @ 3960'. RD. PT csg to 3800 psi/15 min, OK. Perf Menefee/Point Lookout @ 5257, 5268, 5326, 5354, 5356, 5368, 5388, 5399, 5406, 5417, 5418, 5420, 5422, 5424, 5427, 5432, 5450, 5455, 5462, 5470, 5480, 5511, 5520, 5546, 5583, 5639, 5660, 5744 w/28 holes total. Acidize w/1000 gal 15% Hcl. Frac Menefee/Point Lookout w/95,928 gal slk wtr, 100,000# 20/40 Arizona sd. RU, set CIBP @ 5245'. PT CIBP, csg & pkr to 3800 psi, OK. Perf Cliff House/Menefee @ 4790, 4795, 4812, 4816, 4823, 4828, 4834, 4842, 4851, 4872, 4880, 4883, 4893, 4899, 4904, 4908, 4919, 4927, 4960, 4985, 5013, 5020, 5060, 5070, 5117, 5138, 5142, 5174, 5194, 5206 w/30 holes total.
- 6-17-95 Acidize w/1500 gal 15% Hcl. Frac Cliff House/Menefee w/91,434 gal slk wtr, 100,000# 20/40 Arizona sd. Release pkr. RD. TIH, CO to 5245'. Blow well & CO.
- 6-18-95 Blow well & CO. Mill CIBP @ 5245'. Blow well & CO.
- 6-19/20-95 Blow well & CO.
- 6-21-95 TOOH w/mill. RU, ran after frac log @ 4650-5786'. RD. Blow well & CO. TIH w/183 jts 2 3/8" 4.7# J-55 tbq, landed @ 5729'. ND BOP. NU WH. RD. Rig released.