	n <b>9-3</b> 8 eb. 1961	
٢	$\top$	į



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Se	inta 1	fe.
Lease No.	07	19 <b>3</b> 63	
S		Juan	28-6
Unit1	-08	-001	-1051

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	 SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	 SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
	SUBSEQUENT REPORT OF ABANDONMENT
	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	 

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

				·	March 28	, 19. 58
Well No.	80 (PM) is loca	ated 1650 ft. i	rom_ Scrline a	nd 1750 ft. from	n E line of se	c. 12
KE	Sec. 12	27N	6 <b>W</b>	N.M.P.M.	( )	
(1/4 8	Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
Blanc	o M.V., Undes	lg- R	io Arriba	Ne	w Mexico	
	(Field) nated		unty or Subdivision)	(1	State or Territory)	
			<b>(1.3</b> )	• •		

The elevation of the derrick floor above sea level is 6433 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-2%-58. Total Depth 3372'.

Ran 82 joints 7 5/8", J-55, 26.40#, Casing (3357') set at 3367' with 100 sacks regular cement, 100 sacks Pozmix, 50# Flocele and 4% gel, followed with 50 sacks Beat cement, 2% CaCl.

Held 1000# for 30 minutes.

Top of cement by temperature survey at 2500'.

APR 2 1935 OIL CON. C DIST.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company _	El Paso Natural Gas Company	
Address	Box 997	
	Farmington, New Mexico	By Original Signed D. C. Johnston
		Title Petraleum Engineer
		GPO 918507