## Form 9-331a (Feb. 1951)

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No.	42-R358.4.
Form Approved.	
	ፈ

Land Office Santa Fe

079391

Unit San Juan 27-5



## sundry notices and reports on wells $^{\circ}$ $^{1962}$

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHIP OF WITHOUT DEW MEY TOO
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Water Frac.
(INDICATE ABOVE BY CHECK MARK	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
	June 27 19 6
do domb	······································
Well No. 69 (10) is located 1090 ft. from	$1 - {N \choose N}$ line and $\frac{990}{N}$ ft. from ${E \choose N}$ line of sec. $\frac{7}{N}$
BR Section 7 27-H	5-W N.M.P.M.
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
	or Subdivision) (State or Territors)
,,	/ // //
The elevation of the derrick floor above sea le	vel is 5639 ft.
	1902
DETA	ILS OF WORK \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
State names of and expected depths to objective sands; show size	zes, weights, and lengths of proposed casings indicate mudding jobs coment-
(State names of and expected depths to objective sands; show size ing points, and all o	zes, weights, and lengths of proposed casings indicate mudding jobs coment- other important proposed work)
(State names of and expected depths to objective sands; show size ing points, and all on 6-84-62, T.D. 7900°. C.O.T.B. 70	zes, weights, and lengths of proposed casings indicate much ng jobs coment- other important proposed work)  50 • Perf Dekote 760 -08; 7623-32; (4 817)
(State names of and expected depths to objective sands; show size ing points, and all on 6-64-62, T.D. 7900'. C.O.T.D. 7877725-33 (2 SPF), 7772-76 (4 SPF); 76	zes, weights, and lengths of proposed casings indicate mudding jobs coment- other important proposed work)  50'. Perf Bekote 7604-08; 7683-32; (4 817)  316-24 (2 577);
(State names of and expected depths to objective sands; show size ing points, and all of the control of the con	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50'. Perf Bakota 7604-08; 7683-32; (4 SFF)  316-24 (2 SFF);  4 send. Plush w/8400 gallons. I.R. 35
On 6-84-62, T.D. 7900'. C.O.T.D. 76, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac v/69,900 gallons water, 60,000; BFM. Max pr 5300#, EDP 1300#, tr ps	zes, weights, and lengths of proposed casings indicate mudding jobs coment- other important proposed work)  50'. Perf Bekote 7604-08; 7683-32; (4 817)  316-24 (2 577);
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 78 Prac v/69,900 gallons water, 60,000; DPM. Max pr 5300#, EDP 1300#, tr ps B.P. 6 7500'.	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 760-08;7683-32;(4 SFF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400%. Bropped 4 sets of 16 balls. Set
On 6-84-62, T.D. 7900'. C.O.T.D. 787 7725-33 (2 BPF), 7772-76 (4 BPF); 78 Prac w/69,900 gallons water, 60,000; BPM. Max pr 5300#, BBP 1300#, tr ps B.P. 6 7500'.  Perf Point Lockout 5582-86;5618-22;	res, weights, and lengths of proposed casings indicate mudding jobs coment- pother important proposed work)  50'. Perf Bekota 7604-08; 7623-32; (4 817)  316-24 (2 817);  f sand. Flush v/8400 gallons. I.R. 35  r 3400 f. Propped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 817).
On 6-64-62, T.D. 7900'. C.O.T.D. 76, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Prec v/69,900 gallons water, 60,000; BPM. Max pr 5300#, BDP 1300#, tr ps B.P. 6 7500'.  Perf Point Lookout 5582-86;5618-22; Frac v/47,100 gallons water, 44,000	tes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50'. Perf Bakota 7604-08; 7683-32; (4 8FF)  316-94 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac v/69,900 gallons water, 60,000; BPM. Max pr 5300#, BBP 1300#, tr ps B.P. 6 7500'. Perf Point Lookout 5582-86;5618-22; Frac v/47,100 gallons water, 44,000; 60 SPM. Max pr 2200#, BDP 1100#, ta	res, weights, and lengths of proposed casings indicate mudding jobs coment- pother important proposed work)  50'. Perf Bakota 7604-08; 7623-32; (4 817)  316-24 (2 817);  f sand. Flush w/8400 gallons. I.R. 35  r 3400 f. Propped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 817).
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac w/69,900 gallons water, 60,000; BPM. Max pr 5300#, BDP 1300#, tr ps B.P. 6 7500'. Perf Point Lockout 5582-86;5618-22; Frac w/47,100 gallons water, 44,000; 60 BPM. Max pr 2200#, BDP 1100#, ta Set B.P. 6 5300'.	ses, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-06; 7623-32; (4 8FF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.  r pr 2000#. Bropped 3 sets of 16 balls.
On 6-84-62, T.D. 7900'. C.O.T.D. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac v/69,900 gallons water, 60,000; BPM. Has pr 5300#, HBP 1300#, tr ps B.P. 6 7500'.  Perf Point Lookout 5582-86;5618-22; Frac v/47,100 gallons water, 44,000; 60 BPM. Hes pr 2200#, HDP 1100#, ta Set B.P. 6 5300'.  Perf Cliff House 5099-5103;5121-25;	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08;7623-32;(4 SFF)  316-24 (2 SFF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Dropped 4 sets of 16 balls. Set  5648-52;5702-06 (4 SFF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 78, 7725-33 (2 SPF), 7725-76 (4 SPF); 7725-33 (2 SPF), 7725-76 (4 SPF); 7725-76 (4 7725-76 (4 SP	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08;7683-32;(4 SPF)  316-94 (2 SPF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Bropped 4 sets of 16 balls. Set  5648-52;5702-06 (4 SPF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.  5180-84; (4 SPF) 5236-44; (2 SPF)  ad. Flush w/6350 gal water. I.R. 55 BPM.
On 6-84-62, T.D. 7900'. C.O.T.D. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac v/69,900 gallons water, 60,000; BPM. Max pr 5300#, HBP 1300#, tr ps B.P. 6 7500'.  Perf Point Lookout 5582-86;5618-22; Frac v/47,100 gallons water, 44,000; 60 SPM. Max pr 2200#, HDP 1100#, ta Set B.P. 6 5300'.  Perf Cliff House 5099-5103;5121-25;	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08;7623-32;(4 SPF)  316-34 (2 SPF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Bropped 4 sets of 16 balls. Set  5648-52;5702-06 (4 SPF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.  5180-84; (4 SPF) 5236-44; (2 SPF)  ad. Flush w/6350 gal veter. I.R. 55 BPM.
On 6-84-62, T.D. 7900'. C.O.T.D. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76, 7725-33 (2 SPF), 7725-76 (4 SPF); 76, 7725-76 (4 SPF); 76, 7725-76 (4 SPF); 7725-76 (	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08;7623-32;(4 SPF)  316-34 (2 SPF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Bropped 4 sets of 16 balls. Set  5648-52;5702-06 (4 SPF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.  5180-84; (4 SPF) 5236-44; (2 SPF)  ad. Flush w/6350 gal veter. I.R. 55 BPM.
On 6-84-62, T.D. 7900'. C.O.T.D. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76, 7725-33 (2 SPF), 7725-76 (4 SPF); 7725-33 (2 SPF), 7725-36, 7805',	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-06; 7623-32; (4 8FF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52; 5708-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.  r pr 2000#. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush v/6350 gal veter. I.R. 55 BFM.  Bropped 3 sets of 16 balls.
Company  Cate names of and expected depths to objective sands; show sing points, and all of the categories, and all of the catego	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-06; 7623-32; (4 8FF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52; 5708-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.  r pr 2000#. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush v/6350 gal veter. I.R. 55 BFM.  Bropped 3 sets of 16 balls.
On 6-84-62, T.D. 7900'. C.O.T.D. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76, 7725-33 (2 SPF), 7725-76 (4 SPF); 76, 7725-76 (4 SPF); 7725-76 (	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-06; 7623-32; (4 8FF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52; 5708-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.  r pr 2000#. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush v/6350 gal veter. I.R. 55 BFM.  Bropped 3 sets of 16 balls.
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76, 7725-33 (2 SPF), 7725-76 (4 SPF); 76, 7725-76 (4 SPF); 7725-76, 7725-76 (4 SPF); 77	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08; 7625-32; (4 SFF)  316-24 (2 SFF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Dropped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 SFF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush w/6250 gal water. I.R. 55 BFM.  Bropped 3 sets of 16 balls.  a writing by the Geological Survey before operations may be commenced.
On 6-84-62, T.D. 7900'. C.O.T.D. 78 7725-33 (2 SPF), 7772-76 (4 SPF); 76 Frac w/69,900 gallons water, 60,000; BPM. Max pr 5300#, HDP 1300#, tr ps B.P. 6 7500'. Perf Point Lookout 5582-86;5618-22; Frac w/47,100 gallons water, 44,000; 60 BPM. Max pr 2200#, HDP 1100#, tr Set B.P. 6 5300'. Perf Cliff Hame 5099-5103;5121-25; Frac w/42,300 gal water; 44,000# see Max pr 2400#, HDP 900#, tr pr 2100#.  I understand that this plan of work must receive approval in Company HDP 900#.	zes, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bakota 7604-08; 7625-32; (4 SFF)  316-24 (2 SFF);  \$ sand. Flush w/8400 gallons. I.R. 35  r 3400%. Dropped 4 sets of 16 balls. Set  5648-52; 5702-06 (4 SFF).  \$ sand. Flush w/6300 gallons water. I.R.  r pr 2000%. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush w/6250 gal water. I.R. 55 BFM.  Bropped 3 sets of 16 balls.  a writing by the Geological Survey before operations may be commenced.
On 6-84-62, T.D. 7900'. C.O.T.B. 78, 7725-33 (2 SPF), 7772-76 (4 SPF); 76, 7725-33 (2 SPF), 7725-76 (4 SPF); 76, 7725-76 (4 SPF); 7725-76 (	res, weights, and lengths of proposed casings indicate mudding jobs comentother important proposed work)  50°. Perf Bekote 7604-06;7683-32;(4 8FF)  316-24 (2 SFF);  \$ sand. Flush v/8400 gallons. I.R. 35  r 3400#. Dropped 4 sets of 16 balls. Set  5648-52;5708-06 (4 SFF).  \$ sand. Flush v/6300 gallons water. I.R.  r pr 2000#. Bropped 3 sets of 16 balls.  5180-84; (4 SFF) 5236-44; (2 SFF)  ad. Flush v/6850 gal veter. I.R. 55 BFM.  Bropped 3 sets of 16 balls.