


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **079363**
Unit **San Juan 28-6 Unit**
14-08-001-1051



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Water Frac. X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 12, 1957

Well No. **66 (24)** is located **690** ft. from **[N]** line and **1650** ft. from **[E]** line of **11**

NE Sec. 11
(¼ Sec. and Sec. No.)

27N
(Twp.)

6W
(Range)

N.M.P.M.
(Meridian)

Blanco & Wildcat
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **6673** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, cementing points, and all other important proposed work)

- 11-4-57 T. D.-Plug back 5750'. Water fractured Point Lookout perf. int. 5596-5612; 5632-42; 5652-60; 5688-5702; 5724-32 w/2 dynajets/ft. w/56,024 gallons water and 60,000# sand. BD pr. 1000#, max. pr. 3000#, avg. tr. pr. 1000, 1100, 1400, 1700, 2700#. IR 54.5 BPM. Flush 10,000 gallons. 5 Stages w/4 drops of 21 balls each.
- 11-4-57 Temporary bridge plug at 5200'. Water fractured Cliff House perf. int. 5076-86; 5096-5108 w/31,760 gallons water and 40,000# sand. BD pr. 1400#, max. pr. 1500#, avg. tr. pr. 1450#. IR 61.7 bbls./min.
- 11-4-57 Temporary bridge plug at 3800'. Water fractured Pictured Cliffs perf. int. 3424-40, 3460-90' w/2 dynajets/ft. w/22,260 gallons water and 40,000# sand. BD pr. 900#, max. pr. 3000#, avg. tr. pr. 800, 1600, 1750#. IR 44 bbls./min. Flush 1050 gallons. 4 Stages w/3 drops of 16 balls each.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

Farmington, New Mexico

By **Original Signed D. C. Johnson**

Title **Petroleum Engineer**