



(SUBMIT IN TRIPLICATE) ✓

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office **Santa Fe**
Lease No. **079393**
Unit **San Juan 27-5**
14-08-001-950

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....	Water Frac	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 16, 1957

Well No. 25 is located 890 ft. from ~~NN~~ S line and 1000 ft. from ~~EE~~ W line of sec. 3
SW Section 3 27N 5W N.M.P.M.
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6585 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-10-57. Total Depth COTD 5750'. Water fractured Point Lookout perforated intervals 5600-14; 5624-42; 5658-72; 5682-5700; 5720-30 with 70,000 gallons water and 60,000# sand. Breakdown pressure none, none & 3000#, maximum pressure 1700, 1900, 2700#, average treating pressure 1700, 1900, 2700#. Injection rate 51.3 bbls./min. Flush 7000 gallons. Natural gage none. Fraced w/20,000# sand (3 times) divided w/55 balls twice (3 stages)

4-10-57. Temporary Bridge Plug at 5550'. Water fractured Cliff House perforated intervals 5160-70; 5182-92; 5204-16; 5226-36' with 65,000 gallons water and 60,000# sand. Breakdown pressure 1000#, maximum pressure 2100#, average treating pressure 1800#. Injection rate 57.0 bbls./min. Flush 6000 gallons. Natural gage none.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997
Farmington, New Mexico

By Original Signed EWELL

Title Petroleum Engineer

