


Land Office **Santa Fe**
 Lease No. **079363**
 Unit **San Juan 26-6 Unit**
14-08-001-1051

(SUBMIT IN TRIPLICATE)

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY




SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 29, 19 58

Well No. **26 (OWO)** is located **994** ft. from **S** line and **1652** ft. from **W** line of sec.
SW **Sec. 1** **27N** **6W** **N.M.P.M.**
 (¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco **Rio Arriba** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6510** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

10-20-58. Total Depth 5605'. C.O.T.D. 5560'. Water frac. Point Lockout perf. int. (2 dyna jets/ft) 5434-44; 5450-66; 5490-5500; 5506-12; 5520-32 with 51,368 gallons water and 50,000# sand. B.D.P. 800#, max. pr. 2000#, avg. tr. pr. 1600#. I.R. 68 B.P.M. Flush 11,000 gallons. Dropped 3 sets of 20 balls each and 1 set of 10 balls for 5 stages. Temp. B.P. @ 5415'. Water frac. Manafee perf. int. (2 dyna jets/ft) 5176-96; 5240-46; 5298-5316; 5326-34; 5382-88 with 42,000 gallons water and 45,000# sand. B.D.P. 1800#, max. pr. 2100#, avg. tr. pr. 1900#. I.R. 58.3 BPM. Flush 10,000 gallons. Dropped 2 sets of 10 balls each and 1 set of 20 balls for 4 stages. Temp. B.P. @ 5100'. Water frac. Cliff House perf. int. (2 DJ/ft) 4934-52; 4966-74; 4978-88; 5004-36; 5044-68 with 53,000 gal. water & 50,000# sand. BDP 1500#, max. pr. 1825#, avg. tr. pr. 1700#. I.R. 65 BPM. Flush 10,000 gallons. Dropped 4 sets of 35 balls each for 5 stages. Temp. B.P. @ 4885'. Water frac. Pictured Cliffs perf. int. (4 DJ/ft) 3280-3304; 3320-40 with 38,816 gallons water and 45,000# sand. BDP 1500#, max. pr. 1300#, avg. tr. pr. 850#. I.R. 73.6 BPM. Flush 5500 gal. Dropped 3 sets of 40 balls each for 4 stages.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997****Farmington, New Mexico**By **Original Signed D. W. Meehan**Title **Petroleum Engineer**