New Mexico OIL CONSERVATION COMMISSION

Aztec, New Mexico

February 17, 1958

El Paso Natural Gas Co Box 997 Farmington, New Mexico

Att: Mr. E. S. Oberly

Re: El Paso Nat. Gas #82 San Juan Unit 28-7, NE4 Section 4-27N-7W, Rio Arriba Co.

Gentlemen:

This letter will serve as your tentative approval for the dual completion of the above well as a gas-gas dual in the Pictured Cliffs and Mesaverde Formations.


It is understood the well will be equipped as set out in your application. Upon final completion, application for administrative approval should be made to Mr. A. L. Porter in Santa Fe, as instructed in Rule 112.

Yours very truly

Emery C. Arnold Supervisor, Dist. #3

ECA:ks


oc: Mr. A. L. Porter, Jr. OCC. Santa Fe. N.M.







Job separation sheet



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Land Office Santa Te

Lease No. 076496-A

Unit Sen Juan 20-7 Unit 14-03-001-459

RECEIVED

., .

CHAIDDA MOINCE	ND PEDODTS ON WILLS WAY!
SUNDRY NOTICES A	ND REPORTS ON WELLS MAY
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING.	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABOVE BY CHECK MARK NA	ATURE OF REPORT, NOTICE, OR OTHER DATA)
Well No. 52 (FM) is located 1190 ft. from	[N] line and 13.90 ft. from Experime of sec. 4
MV D	nge) (Meridian)
Blanco & So. Blanco Ext. Rio Asmit	()
(Field) (County or Se	
State names of and expected depths to objective sands, show since	S OF WORK weights, and lengths of proposed casings; indicate mudding jobs, cement- rimportant proposed work)
2-3-53. Total Depth 5722' Ran 55 Joints 5 1/2", 15.50%, J-55 lin Backs regular cement, 125 macks Pozsdx Backs regular cement.	er (2309') set from 3409 to 9718' with 12 , 40 30', 1/8# Flocele/sk, followed by 50
hald looky for 30 minutes.	
lop of cement by temperature survey at	5100°.
I understand that this plan of work must receive approval in writing the second state of the company ompany	ing by the Geological Survey before operations may be commenced.
ddress Box 997	
Fermington, New Hexico	By H.E. MCANALLY
	Title Petroleum Engineer