

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079491
Unit See Jan 2/-5 Unit
14-U-001-950

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 14, 1960

Well No. 15-1 is located 100 ft. from N line and 100 ft. from E line of sec. 1


N 1/4 Sec. 1 (1/4 Sec. and Sec. No.)
El Paso (Twp.)
El Paso (Range)
El Paso (Meridian)
El Paso Mesa Verde (Field)
Rio Arriba (County or Subdivision)
New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7330 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 5 P. M. 5-31-60.
On 5-1-60 Total Depth 295'. For 7 joints 10 3/4" S. W. surface casing (295') set at 295'.
(1) Volume of cement used - 336 C. F.
(2) Mixture Used: 100 Regular Class A cement 90% Portland C containing 10% SA
(3) Temperature of slurry when mixed 60°.
(4) Formation temperature - 70°.
(5) Strength of cement in 12 hours - 507 psi.
(6) Time cement was in place when tested - 12 hours.
Casing held 600 psi/30 minutes.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 950

Farmington New Mexico

By ORIGINAL SIGNED B.H. MEANS

Title Petroleum Engineer

