## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	<del></del>			
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REOF CASING SH	ESULT OF TEST UT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RE	ECOMPLETION	REPORT ON (Other) Water Fracture	x
	***************************************	cember 16, 1955	Fermington, New Me	xico
Following is a report on the wor	,-	nate) ined under the heading note	(Place) ed above at the	
El Paso Hatur	al Gas Company	San Jus	un 28-7 Unit	
		, Well No	.in the	2
T. 2711 , R. 7W , NMPM.,	•	Pool,	Rio Arriba	County.
The Dates of this work were as follows:	12-14-55			
Notice of intention to do the work (wa	s) (was not) submitted on Fo	orm C-102 on		, 19
		(C	ross out incorrect words)	,
Set Baker bridge plug	LLED ACCOUNT OF WOR	ted with 4 jet she	ots/ft. 4450' - 4470',	
Set Baker bridge plug 4488' - 4506', 4514' - same intervals as above 1350 psi, maximum preserve 44.3 bbls./min.	at 4950'. Perform 4550', 4590' - 466 e with 55,070 gallo sure 1700 psi. Ave Flush with 5000 gal	ted with 4 jet sho 04'. Water fractions water and 55,6 erage treating pro- llens water.	ots/ft. 4450' - 4470', pred Cliff House foresti 000f sand. Breakdown pro- essure 1600 psi, Inject OEC 191955 OIL COM. COM. DIST. 3	ion
Set Baker bridge plug hh88' - 4506', 4514' - same intervals as abov 1350 psi, maximum pres	at 4950'. Perform 4550', 4590' - 466 e with 55,070 gallo sure 1700 psi. Ave Flush with 5000 gal	ted with 4 jet sho 04'. Water fractions water and 55,0 erage treating pro	ots/ft. 4450' - 4470', pred Cliff House foresti 000f sand. Breakdown pro- essure 1600 psi, Inject OEC 191955 OIL COM. COM. DIST. 3	ion

Oil