## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other) Water Fracture
	Beccuber 16, 1955	Farmington, New Mexic
	(Date)	(Place)
1	done and the results obtained under the heading	
(Company or Op	perator)	Juan 28-7 Unit
C. M. Carroll	, Well No,	in the 1/4 of Sec
T. 271 , R. 7V., NMPM.,	Blanco Pool,	Rio Arriba
The Dates of this work were as follows:	12-13-55	
	•	•
Notice of intention to do the work (was	(was not) submitted on Form C-102 on	(Cross out incorrect words)
and approval of the proposed plan (was	(was not) obtained.	
DETAI	LED ACCOUNT OF WORK DONE AND RES	note/ft. 5001! - 5078!. 5058!
On 12-13-55 C.O. Depth 5069', 5020' - 5043', 5 same interval as above 900 psi, maximum pressu		nots/ft. 5091' - 5078', 5058' Water fractured Point Locksut 0.000# sand. Breakdown press
On 12-13-55 C.O. Depth 5069', 5020' - 5043', 5 same interval as above 900 psi, maximum pressu	5095'. Perforated with 4 jet al 5096' - 4994' & 4964' - 4984'. I with 52,500 gallens water and 60 are 1500 psi, average treating p	nots/ft. 5091' - 5078', 5058' later freetured Point Lockout 0,000f sand. Breckdown pressure 1400 psi. Injection  OEC 19185  OIL CON. CON. DIST. 3
On 12-13-55 C.O. Depth 5069', 5020' - 5043', 5 same interval as above 900 psi, maximum pressurate 54.9 bbls./min. I	TI Pase Matural Gas C  (Company)  I hereby certify to the best of me	ots/ft. 5091' - 5078', 5058' leter freetured Point Lockeut 0,000f sand. Breakdown press ressure 1400 psi. Injection OIL CON. CON. DIST. 3  Company Petroleum Engine (Title)
Cn 12-13-55 C.O. Depth 5069', 5020' - 5043', 5 same interval as above 900 psi, maximum pressurate 54.9 bbls./min. I	5095'. Perforated with 4 jet al 5006' - 4994' & 4964' - 4984'. I with 52,500 gallens water and 6 ire 1500 pei, average treating perforated with 5000 gallens.  El Pase Matural Gas C (Company)	ots/ft. 5091' - 5078', 5058' leter freetured Point Lockeut 0,000f sand. Breakdown press ressure 1400 psi. Injection OIL CON. CON. DIST. 3  Company Petroleum Engine (Title)