

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1460' FSL, 1150' FEL, Sec. 15, T-27-N, R-5-W, NMPM, Rio Arriba County

API # (assigned by OCD)

30-039-20046

5. Lease Number

Fee

6. State Oil & Gas Lease #

7. Lease Name/Unit Name

San Juan 27-5 Unit

8. Well No.

108

9. Pool Name or Wildcat

Basin Dakota

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

11-8-96 MIRU. ND WH. NU BOP. TIH, tag CIBP @ 7562'. TOOH to 7561'. Pump 40 bbl wtr ahead. Plug #1: pump 12 sx Class "B" neat cmt @ 7402-7561'. TOOH to 2381'. SD for weekend.

11-11-96 TOOH w/237 jts 2 3/8" tbgs. TIH, perf 3 sqz holes @ 6370'. TOOH. TIH w/4 1/2" cmt retainer, set @ 6318'. PT tbgs to 1500 psi/10 min, OK. Load csg w/15 bbl wtr. Establish injection. Plug #2: pump 43 sx Class "B" cmt outside csg below cmt retainer @ 6270-6370'. Pump 8 sx Class "B" cmt on top of cmt retainer inside csg to 6220'. TOOH to 5238'. Establish circ. Plug #3: pump 13 sx Class "B" neat cmt @ 5064-5238'. TOOH to 3523'. Establish circ. Plug #4: pump 31 sx Class "B" neat cmt @ 3114-3523'. TOOH to 3110'. Plug #5: pump 31 sx Class "B" neat cmt @ 2701-3110'. TOOH to 2697'. Reverse circ 25 bbl cmt to surface. TOOH to 1427'. SDON.

11-12-96 TIH, tag plug #4 @ 2840'. TOOH to 2825'. Load hole w/5 bbl wtr. PT csg to 500 psi, failed. Plug #6: pump 12 sx Class "B" neat cmt inside csg @ 2667-2825'. TOOH to 1586'. WOC. TIH, tag plug #6 @ 2696'. TOOH to 1650'. Perf 3 sqz holes @ 1650'. TOOH. TIH w/4 1/2" cmt retainer, set @ 1590'. TOOH. TIH, establish injection. Plug #7: pump 57 sx Class "B" cmt below cmt retainer outside csg @ 1550-1650'. Pump 7 sx Class "B" cmt on top of cmt retainer to 1498'. TOOH. TIH, perf 3 sqz holes @ 387'. TOOH. Establish circ down csg & out bradenhead. Plug #8: pump 179 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. SDON.

11-13-96 ND BOP. Cut off WH. Fill 4 1/2" csg & 4 1/2" x 9 5/8" annulus w/28 sx Class "B" cmt. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 11-13-96. (Ernest Cardona, OCD on location).

SIGNATURE

Regulatory Administrator December 3, 1996

(This space for State Use)

Approved by

Title

Date

1-15-97