

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1150' FNL, 950' FEL, Sec. 10, T-27-N, R-5-W, NMPM

DHC-2303

5. Lease Number
SF-079491A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-5 Unit

8. Well Name & Number

San Juan 27-5 U #113

9. API Well No.

30-039-20201

10. Field and Pool

Blanco MV/Basin DK

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☒ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Commingle

13. Describe Proposed or Completed Operations

7-27-99 MIRU. SDON.

7-28-99 ND WH. NU BOP. TOOH w/220 jts 2 3/8" tbg. TIH w/4 1/2" CIBP & pkr, set CIBP @ 6850'. Load hole w/wtr. Circ hole clean. PT CIBP to 3000 psi/15 min, OK. Release pkr. PT csg to 3000 psi/15 min, OK. TOOH w/pkr. TIH w/4 1/2" pkr, set @ 62'. PT csg below pkr to 3000 psi/15 min, OK. TOOH w/pkr. TIH, ran CBL @ 4500-6848', TOC @ 4470'; 90-100% bond @ 6580-6848'. TOOH. SDON.

7-29-99 ND BOP. NU WH. RD. Rig released.

7-30-99 MIRU. TIH, perf lower Menefee/Point Lookout @ 6250, 6253, 6285, 6290, 6297, 6341, 6352, 6365, 6382, 6402, 6420, 6447, 6471, 6497, 6510, 6548, 6578, 6600, 6618, 6630, 6646, 6662, 6678, 6696' w/0.32" diameter holes. Frac lower Menefee/Point Lookout w/12,500 gal slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/CIBP, set @ 6220'. PT CIBP to 3000 psi, OK. Perf Cliff House/upper Menefee w/1 SPF @ 5735, 5752, 5770, 5783, 5805, 5825, 5846, 5872, 5890, 5918, 5942, 5959, 5970, 5978, 6040, 6051, 6063, 6069, 6082, 6098, 6108, 6120, 6127, 6153, 6180, 6186, 6189' w/27 0.32" diameter holes total. Acidize w/1050 gal 15% HCl. Frac Cliff House/upper Menefee w/12,500 gal slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/CIBP, set @ 5650'. PT CIBP to 3000 psi, OK. TOOH. TIH, perf Lewis w/1 SPF @ 4989, 4992, 4998, 5006, 5011, 5016, 5133, 5138, 5146, 5166, 5172, 5180, 5185, 5192, 5199, 5220, 5225, 5230, 5232, 5299, 5304, 5310, 5320, 5325, 5330, 5335, 5346, 5352, 5363, 5370, 5374, 5381, 5505, 5510, 5520, 5526, 5536, 5542, 5548, 5552' w/40 0.29" diameter holes total. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator

Date 8/19/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date

SEP 09 1999

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make a false statement or representation to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

44MOC0

3-1-99 Acidize w/10% acetic acid. Frac Lewis w/40,000 gal 75 Quai foam, 200,000# 20/40 Arizona sd.
8-2/4-99 Blow well & CO. RD.
8-9-99 MIRU. TIH w/CIBP, set @ 2000'. ND BOP. Change out well head. NU BOP. TIH w/3 7/8" mill to CIBP @ 2000'.
8-10-99 Drill out CIBP @ 2000'. TIH, tag up @ 5474'. Blow well & CO to 5650'. Drill out CIBP @ 5650'. Blow well & CO.
8-11-99 Blow well & CO to 6210'. Drill out CIBP @ 6210'. Blow well & CO.
8-12-99 TIH, tag up @ 6403'. Blow well & CO to 6850'.
8-13-99 Blow well & CO. Drill out CIBP @ 6850'.
8-14-99 TIH, blow well & CO to PBTD @ 8637'.
8-15-99 Blow well & CO.
8-16-99 Blow well & CO. TOOH. TIH w/275 lbs 2 3/8" 4.7# J-55 EUE tbgs, landed @ 8496'. ND BOP. NU WH. RD. Rig released.

Well will produce as a Mesaverde/Dakota commingle under DHC-2303