

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS	DHC-2302	API # (assigned by OCD) 30-039-20228
		5. Lease Number
2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY LP		6. State Oil&Gas Lease # E-290-19
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700		7. Lease Name/Unit Name San Juan 27-5 Unit
4. Location of Well, Footage, Sec., T, R, M 1840' FSL, 800' FWL, Sec.16, T-27-N, R-5-W, NMMP, Rio Arriba County		8. Well No. 40
		9. Pool Name or Wildcat Blanco MV/Basin DK
		10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☒ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☒ Altering Casing
	☒ Other -

13. Describe Proposed or Completed Operations

2-27-02 MIRU. PT 4 1/2" csg to 4100 psi, OK. RD
2-28-02 MIRU. Perf Dakota w/1 SPF @ 7458-7498', 7588-7612', 7566-7572', 7628-7634', 7641-7658', 7498-7502', 7665-7691' w/129 0.28" diameter holes total. RD.
3-1-02 Acidize w/25 bbl 15% HCl. Frac Dakota w/2328 bbl slk wtr, 40,000# 20/40 tempered LC sd. TOOH. TIH w/4 1/2" CIBP & pkr, set CIBP @ 7408'. PT CIBP to 4100 psi/10 min, OK. TOOH w/pkr. Perf lower Menefee/Point Lookout w/1 SPF @ 5389, 5395, 5403, 5413, 5423, 5432, 5441, 5446, 5452, 5462'. Perf w/2 SPF @ 5477, 5491, 5505, 5513, 5520, 5536, 5552, 5564, 5572, 5578, 5600, 5661, 5748, 5786, 5808' w/40 0.28" diameter holes total. Acidize w/25 bbl 15% HCl. Frac lower Menefee/Point Lookout w/2014 bbl slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/4 1/2" frac plug & pkr, set frac plug @ 5355'. PT to 4100 psi/10 min, OK. TOOH w/pkr. TIH, perf Cliff House/upper Menefee w/1 SPF @ 4823, 4834, 4848, 4859, 4866, 4917, 4926, 4932, 4956, 4966, 4978, 4993, 5007, 5016, 5024'. Perf w/2 SPF @ 5081, 5101, 5122, 5144, 5168, 5181, 5205, 5218, 5286, 5313' w/35 0.28" diameter holes total. Acidize w/25 bbl 15% HCl. Frac Cliff House/upper Menefee w/2072 bbl slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/4 1/2" frac plug & pkr, set frac plug @ 4765'. PT frac plug to 4100 psi/10 min, OK. TOOH w/pkr. TIH, perf Lewis w/1 SPF @ 3972, 4008, 4096, 4113, 4127, 4142, 4157, 4222, 4236, 4246, 4252, 4260, 4270, 4297, 4316, 4329, 4343, 4391, 4399, 4407, 4421, 4433, 4457, 4491, 4524, 4530, 4545, 4576, 4587, 4620, 4631, 4638, 4674, 4685, 4695, 4701, 4712' w/37 0.28" diameter holes total. SDON.

Continued on back

SIGNATURE *Regina Calk* Regulatory Supervisor March 28, 2002

no
(This space for State Use)

Approved by *[Signature]* Title _____ Date APR -2 2002

3-2-02 Acidize w/2050 gal 15% HCl. Frac Lewis w/685 bbl 20# linear gel, 200,000# 20/40
Arizona sd. Blow well & CO.
3-3/4-02 Blow well & CO. RD.
3-6-02 MIRU. ND WH. NU BOP. TIH w/3 7/8" mill to 2898'. Blow well & CO. Establish circ.
Mill out frac plug @ 4765'. Blow well & CO.
3-7-02 Blow well & CO to 5119'. Establish circ. Mill out frac plug @ 5355'. TIH, blow
well & CO.
3-8/10-02 Blow well & CO.
3-11-02 Blow well & CO. TIH, blow well & CO @ 7253'. Establish circ. Mill out CIBP @ 7408'.
Blow well & CO.
3-12-02 Blow well & CO to PBTD @ 7737'.
3-13-02 Blow well & CO. TOOH w/mill. TIH, blow well & CO.
3-14/18-02 Blow well & CO. SDON.
3-19-02 TOOH. TIH, blow well & CO.
3-20/26-02 Blow well & CO to PBTD @ 7737'.
3-27-02 Blow well & CO. TOOH. TIH w/235 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 7371'.
(SN @ 7369'). ND BOP. NU WH. SDON.
3-28-02 RD. Rig released.

Well will produce as a Mesaverde/Dakota commingle under DHC-2302