

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 4289, Farmington, NM, 87499-4289

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1850' FNL, 790' FWL, Sec. 19, T27N  
AT TOP PROD. INTERVAL: R7W  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

**RECEIVED**  
JUN 13 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF 078840  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
San Juan 28-7 Unit  
9. WELL NO.  
#148  
10. FIELD OR WILDCAT NAME  
So. Blanco Pictured Cliffs  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit E, Sec. 19, T27N, R7W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6588' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1) Spotted 43 sacks cement and covered PC formations, Fruitland formation, and Ojo Alamo formation from PBTB @ 2993' up through 1980' (100' above Ojo Alamo top).
- 2) Perforated 4 squeeze holes @ 185' (50' below surface casing) and circulated 60 sacks of cement to surface.
- 3) Installed dry hole marker.

**RECEIVED**

DEC 27 1984

OIL CON. DIV.  
DIST. 3

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donal W. Munro TITLE Engineer DATE June 10, 1983

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

**APPROVED  
AS AMENDED**

DEC 20 1984

M. MILLENBACH  
AREA MANAGER

Approved as to plugging of the well bore. \*See Instructions on Reverse Side  
Liability under bond is retained until  
surface restoration is completed.