1	

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	LEASE	
	SF	078640

CHRIDDY	NOTICES	AND	DEDODTE	ON	WELLC
20MDK1	MOTICES	ANU	REPORTS	UN	AA E L L L

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

1. oil gas XX other

2. NAME OF OPERATOR El Paso Natural Gas Company

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE

(other) Casing Repair

REPAIR WELL

CHANGE ZONES ABANDON*

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1090'N, 1450'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 28-7 Unit

8. FARM OR LEASE NAME San Juan 28-7 Unit NP

9. WELL NO. 151

10. FIELD OR WILDCAT NAME Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 21, T-27-N, R-7-W NMPM

12. COUNTY OR PARISH 13. STATE
Rio Arriba New Mexico

14. API NO

15. ELEVATIONS (SHOW DF, KDB, AND WD)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- 4-21-82: MOL & RU. Released packer and TOOH w/ 254 joints of 2 3/8" tubing. Set 4 1/2" top drillable bridge plug at 7200'. TIH w/ 4 1/2" RTTS packer. Isolated casing failure in 4 1/2" casing between 653' and 741'.
- 4-22-82: Welded a 4' piece of 4 1/2" casing on top of cut off attached cementing head and mixed cement. Squeezed w/ 507 cf. cement. Circ. to surface cleaned out squeeze cmt. Pressure tested to 1000#, Held ok.
- 4-23-82: Ran 253 joints of 2 3/8", 4.7#, K-55 tubing set at 7482'. S.N. set at 7208'. Otis Perma Latch Packer set at 7209'.

NWOCC

Subsurface Safety Valve: Manu. and Type

18. Thereby cortify that the foregoing is true and correct

SIGNED TITLE Drilling Clerk DATE May 4, 1982

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORDITLE DATE

MAY 101982

MAY 101982

FARMINGTON DISTRICT *See Instructions on Reverse Side