Fc.m 9-331 (M:.y 1963)	DEPARTMENT OF THE INTERIOR (Other Instructions on					
	NDRY NOTI	EOLOGICAL SURVE  CES AND REPOR  Us to drill or to deepen or	rs on wells	6. IF INDIAN, ALLOTTE		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT" for such proposals.)				7. UNIT AGREEMENT NAME		
OIL GAS WELL OTHER  2. NAME OF OPERATOR				San Juan 28-6 Unit		
El Paso Natural Gas Company				San Juan 28-6 Unit		
3. ADDRESS OF OPERATOR				9. WELL NO.		
	Farmington	166 10. FIELD AND POOL, OR WILDCAT				
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  810'S, 875'W				Basin Dakota 11. SEC., T., E., M., OR BLK. AND SUBVEY OR AREA Sec. 1, T-27-N, R-6-W NMPM		
14. PERMIT NO.		15. ELEVATIONS (Show whet	her DF, RT, GR, etc.) 6494'GL	Rio Arriba	New Mexico	
16.	Check Ap	propriate Box To Indica	ate Nature of Notice, Report, or C	Other Data		
NOTICE OF INTENTION TO:				QUENT REPORT OF:		
TEST WATER SHUT	r-off P	ULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING	WELL	
FRACTURE TREAT	, c	IULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING (	CASING	
SHOOT OR ACIDIZE	[	BANDON*	SHOOTING OR ACIDIZING	ABANDONMI	ENT*	
REPAIR WELL	c	HANGE PLANS	(Other)	of multiple completion letion Report and Log fo	on Well	
(Other)  17. DESCRIBE PROPOSED	OR COMPLETED OPE	RATIONS (Clearly state all pe	rtinent details, and give pertinent dates, locations and measured and true vertice			
proposed work. nent to this work	i.) *					
5-18-72	Cemented	T.D. 3563'. Ran 112 joints 7", 20#, KE intermediate casing, 3550' set at 3563'. Cemented with 234 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2320'.				
5-23-72	T.D. 7748'. Ran 250 joints 4 1/2", 11.6 and 10.5#, KS production casing, 7736' set at 7748'. Float collar set at 7739'. Cemented with 647 cu.ft. cement. WOC 18 hours. Top of cement at 3000'.					
7-20-72	7-20-72 PBTD 7739'. Perf'd 7498-7510', 7606-18', 7650-56', 7670-76', 7686-92 7702-08' with 12 shots per zone. Frac'd with 56,000# 40/60 sand and 5' treated water. Drop six sets of 12 balls each. Flushed with 5208 gallon					
			SETEIVED		IVEM	
			TANKE TO TO	JUL 26	1972	
,	, \		JUL 27 1972 OIL CON. COM. DIST. 3	U. S. GEOLOGICA DURANGO, C	OTO' Sayasa	
18. I hereby century the	tylihe foregoing is	true and correct	Petroleum Engine	er DATE July 2	4, 1972	
(This space for F	ederal or State offic	ce use)				
APPROVED BY _ CONDITIONS OF	APPROVAL, IF A	NY:		DATE		