

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen a well on a different reservation.
Use "APPLICATION FOR PERMIT" for such proposals.

SUBMIT IN TRIPLICATE TO DISTRICT OFFICE, FARMINGTON, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Union Oil Company of California

3. Address and Telephone No.

3300 N. Butler, Suite 200, Farmington, NM 87401 (505)326-7600

4. Location of Well: Footage, Sec., T., R., M., or Survey Description:

1650' FSL, 1650' FWL

Sec. 35, T27N, R7W

5. Lease Designation and Serial No.

SF 080385

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Rincon Unit

8. Well Name and No.

193

9. API Well No.

30-039-20500

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☒ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

A casing leak was squeeze cemented on the subject well in March of 1992 as follows:

- 3/21/92 Set retrievable bridge plug at 7015'. Isolated casing leak between 323' and 448' KB.
3/24/92 Squeeze leak with 214 sx of Class B cement containing 2% Calcium Chloride. Squeezed to 1200 psi and left well shut in.
3/25/92 Drilled out cement and pressure tested squeeze to 2050 psi. Held OK.
3/26/92 Retrieved bridge plug at 7015'.
3/27/92 Ran 2 3/8" tubing and landed at 7391' KB. Returned well to production.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date 4/19/93

(This space for Federal or State use)

Field Superintendent

ACCEPTED FOR RECORD

Approved by

Title

Date

Conditions of approval, if any:

APR 26 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

BY

NMOCD