

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well GAS</p> <hr/> <p>2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY LP</p> <hr/> <p>3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <hr/> <p>4. Location of Well, Footage, Sec., T, R, M 1700' FNL, 790' FWL, Sec.19, T-27-N, R-4-W, NMPM, Rio Arriba County</p>	<p>API # (assigned by OCD) 30-039-20670</p> <p>5. Lease Number Fee</p> <p>6. State Oil&Gas Lease #</p> <p>7. Lease Name/Unit Name San Juan 27-4 Unit</p> <p>8. Well No. 64</p> <p>9. Pool Name or Wildcat Tapacito Pict Cliffs</p> <p>10. Elevation:</p>
--	--

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

4-23-02 MIRU. SDON.

4-24-02 ND WH. NU BOP. PT BOP. TIH w/2 7/8" gauge ring to 2698'. TOOH. TIH, tag up @ 3116'. Establish circ. Circ hole clean to 3502'. (Verbal approval to change plans from Henry Villeneuve, OCD). Plug #1: pump 25 sx Class "B" neat cmt inside csg @ 2592-3502' to cover Pictured Cliffs perfs, Fruitland, Kirtland & Ojo Alamo intervals. TOOH. WOC. SDON.

4-25-02 TIH, tag TOC @ 2795'. Load csg w/1 bbl wtr. PT csg to 500 psi/15 min, OK. TOOH. TIH, perf 2 sqz holes @ 1840'. Establish injection. TOOH. TIH w/cmt retainer, set @ 1795'. Establish injection. Plug #2: pump 35 sx Class "B" neat cmt outside csg, below cmt retainer @ 1740-1840' to cover Nacimiento interval. Pump 6 sx Class "B" neat cmt inside csg @ 1617-1795'. TOOH. TIH, perf 2 sqz holes @ 190'. Establish circ down 2 7/8" csg & out bradenhead w/10 bbl wtr. Plug #3: pump 88 sx Class "B" neat cmt down 2 7/8" csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Found cmt @ surface. Install dry hole marker w/15 sx Class "B" neat cmt. SDON.

4-26-02 RD. Rig released.

Well plugged and abandoned 4-25-02.

SIGNATURE *Peggy Cole* Regulatory Supervisor May 14, 2002

no
(This space for State Use)

ORIGINAL SIGNED BY REGULATORY SUPERVISOR

DEPUTY REG. SUPERVISOR

NOV 14 2002

Approved by _____ Title _____ Date _____