

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well DHC-2296
GAS

2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
790' FNL, 840' FEL, Sec. 36, T-27-N, R-5-W, NMPM, Rio Arriba County

5. Lease Number
30-039-20686

6. State Oil & Gas Lease #
E-290-3

7. Lease Name/Unit Name
San Juan 27-5 Unit Well No. 147

9. Pool Name or Wildcat
Blanco MV/Basin DK

10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☒ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Commingle

13. Describe Proposed or Completed Operations

9-13-99 MIRU. ND WH. NU BOP. SDON.

9-14-99 TOOH w/272 jts 2 3/8" tbg. TIH w/4 1/4" CIBP & pkr, set CIBP @ 6800'. Load hole w/100 bbl 2% KCl wtr. Circ hole clean. PT CIBP to 3000 psi, OK. PT csg to 3000 psi/10 min, OK. SDON.

9-15-99 SD for rig repair.

9-16-99 TOOH. TIH, ran CBL @ 3200-6800', TOC @ 4890'. 90-100% bond @ 5900-6800', 75-80% bond @ 5100-5900', 50-60% bond @ 4890-5100'. TOOH. TIH, ran GR @ 4890-6800'. TOOH. SDON.

9-17-99 ND BOP. NU WH. RD. Rig released.

9-18-99 MIRU. Perf lower Menefee/Point Lookout w/2 SPF @ 6410, 6430, 6473, 6506, 6552, 6578, 6600, 6615, 6635', w/1 SPF @ 6163, 6166, 6170, 6203, 6212, 6258, 6265, 6282, 6295, 6318, 6321, 6362, 6381, 6392' w/23 0.32" diameter holes total. Acidize w/34 bbl 15% HCl. Frac lower Menefee/Point Lookout w/1954 bbl 2% KCl slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/CIBP, set @ 6100'. PT csg & CIBP to 3000 psi, OK. Perf Cliff House/upper Menefee w/1 SPF @ 5621, 5639, 5656, 5668, 5679, 5696, 5713, 5730, 5745, 5770, 5789, 5807, 5827, 5835, 5849, 5858, 5872, 5883, 5893, 5909, 5926, 5942, 5947, 5992, 6019, 6043, 6045 w/27 0.32" diameter holes total. Acidize w/25 bbl 15% HCl. Frac Cliff House/upper Menefee w/1975 bbl 2% KCl slk wtr, 100,000# 20/40 Arizona sd. TOOH. TIH w/CIBP, set @ 5560'. PT csg & CIBP to 3000 psi, OK. TIH, perf Lewis w/1 SPF @ 5100, 5104, 5108, 5115, 5120, 5125, 5148, 5151, 5155, 5159, 5240, 5244, 5250, 5258, 5262, 5268, 5275, 5289, 5292, 5311, 5314, 5318, 5323, 5325, 5340, 5342, 5346, 5388, 5392, 5400, 5404, 5446, 5450, 5459, 5469, 5477, 5482, 5489' w/38 0.32" diameter holes total. Acidize w/30 bbl 10% acetic acid. Frac Lewis w/792 bbl 20# linear gel, 200,000# 20/40 Arizona sd, 1,289,924 SCF N2. CO after frac.

Continued on back

SIGNATURE Nancy Oltrmanns -for Regulatory Administrator October 4, 1999

no
(This space for State Use)

Approved by ORIGINAL SIGNED BY ERNIE BUSCH Title DEPUTY OIL & GAS INSPECTOR, DIST. 3 Date OCT 6 1999

9-19/20-99 Blow well & CO. RD.
9-24-99 MIRU. ND WH. NU BOP. TIH w/4 ½" RBP, set @ 83'. Change out WH. TOOH w/4 ½" RBP. TIH
w/3 7/8" mill to 4300'.
9-25-99 TIH to 5560'. Blow well & CO. Mill out CIBP @ 5560'. TIH to 6100'. Blow well & CO.
9-26-99 TIH, blow well & CO.
9-27-99 Blow well & CO. Mill out CIBP @ 6100'. TIH to 6800'. Blow well & CO.
9-28/29-99 Blow well & CO.
9-30-99 Blow well & CO. Drill out CIBP @ 6800'. Blow well & CO to PBTD @ 8533'.
10-1-99 Blow well & CO. TOOH w/mill. TIH, blow well & CO.
10-2-99 Blow well & CO. TOOH. TIH w/270 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 8479'. ND BOP.
NU WH. RD. Rig released.

Well will produce as a Mesaverde/Dakota commingle under DHC-2296.