

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT TO DRILL SUCH PROPOSALS"

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Union Oil Company of California

3. Address and Telephone No.

3300 N. Butler, Suite 200, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1651' FSL & 1500' FWL

33-27N-7W

5. Lease Designation and Serial No.

SF 080213

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Rincon Unit

8. Well Name and No.

Rincon Unit

9. API Well No.

200

10. Field and Pool, or Exploratory Area

Otero Chacra

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well P&A'd as per BLM approved procedure.

4/17/91 MIRU Bedford P&A rig.

TIH with 1 1/4" tubing. Spot 20 sx (24 ft³) class "B" cement from 3966'-3240'. Tagged cement top at 3531'. At 3531' spot 50 sx (59 ft³) class "B" cement. Tag top of cement at 1860'. Circulate hole with 9.0 ppg mud. Shoot 4 squeeze holes at 1134'. TIH with 1 1/4" tubing to 1134'. Pumped 56 sx out perfs (66 ft³) and left 4 sx (4.7 ft³) in casing from 1134'-984'. Shoot 4 squeeze holes at 173'. Pumped 60 sx (71 ft³) class "B" cement down casing and circulate 10 sx to surface. Cut off casing. Set P&A marker.

4/18/91 Release rig.

Location will be rehabed when appropriate.

Approved as to plugging of the well hole.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed S.G. Katirgis

Title Petroelum Engineer

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

APPROVED

Date 4/23/91

APR 25 1991

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

FARMINGTON RESOURCE AREA