UNITED STATES SUBMIT IN TRIPLICATE® (Other Instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY								
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)					6. IF IN	NDIAM, ALLOTTER OR	TRIBE NAME	
	X OTHER			RECEIVEN	San	Juan 28-7 Ur	7 nit	
El Paso Natural Gas Company						I OR LEASE NAME Juan 28-7 Ur	nit -	
TAN B						L NO.		
PO Box 990, Farmington, NM 87401							1 6	
4. LOCATION OF WELL (Report location clearly and in accordance with any State required No. COM.						LD AND POOL, OR WI	LDCAT	
See also space 17 below.) At surface 1550'N, 1750'E DIST. 3						Basin Dakota 11. sec., T., R., M., OR BLK. AND		
						Sec. 1, T-27-N, R-7-W		
				•	NM			
14. PERMIT NO.	····	15. ELEVATIONS (Show		RT, GR, etc.)		NTY OR PARISH 13		
-		513	31'GL		Rio	Arriba N	<u>M</u>	
16.	Check Ap	propriate Box To 1	ndicate N	ature of Notice, Report, or	Other Do	ata .		
×	OTICE OF INTENT	10N TO:		8088	EQUENT REPO	ORT OF:		
TEST WATER SHUT-OF	P P	ULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRING WELL		
FRACTURE TREAT	м	ULTIPLE COMPLETE		FRACTURE TREATMENT	<u>X</u>	ALTERING CASIN	G	
SHOOT OR ACIDIZE		BANDON*		SHOOTING OR ACIDIZING		ABANDONMENT*		
REPAIR WELL	c	HANGE PLANS		(Other) (Nore: Report resu	lts of multi	ple completion on 1	Well	
(Other)	COMPLETED OPER	ATIONS (Clearly state	all pertinent	Completion or Recor	npletion Rep	port and Log form.)	starting any	
proposed work. If nent to this work.) *	well is direction	ally drilled, give sub	surface locat	ions and measured and true ver	tical depths	for all markers an	d zones perti-	
11-8-73				#, J-55 intermediate			3171'.	
	Cemented	with 261 cu.f	t. ceme	nt. WOC 12 hours, h	neld 120	0#/30 min.		
	Top of ce	ment at 2050'.		•	::AE14			
							= 117	
11-15-73		268'. Ran 223 joints 4 1/2", 10.5 and 11.6 #, J-55					ıg,	
	7257' set at 7268'. Float collar set at 7261'. Cemented cement. WOC 18 hours. Top of cement at 4600'.					h 653 cu. ft.		
	cement.	WOC 18 hours	s. Top	of cement at 4600'.				
10 05 50	DDDD 70/	11		4000# OV D	461 706			
12-27-73			_	4000#-OK. Perf'd 70				
	-			.6', 7232' and 7248' v 60 sand and 90,220 g				
		-		290 gallons water.	arrons ti	Z 202		
	NO Dall G	.ops. Tushee	WILL DE	70 ganons water.			1271	
					II W LES			
				k, :	4078			
			-	JAN 4	1974		्रेड	
		•		and and	as comació			
•				v. s. Geologia Clarena,				
18. I hereby certify that	the foregoing is	true and correct			· · · · · ·			
SIGNED 21.	· file	<u> </u>	TITLE D	rilling Clerk	r	January 3	3, 1974	
(This space for Feder	ral or State offic	e use)						
APPROVED BY		r	TITLE		r	DATE		
CONDITIONS OF AR	PROVAL, IF A					- 3 ಕಿ ಟ್ಟಿಕಿ - ೩	ನಿಎಚೆ	

14