S

UNITED STATES SUBMIT IN TRIPLICATE.

DEPARTMENT OF THE INTERIOR (Other Instructions on re-	5. LEASE DESIGNATION AND SERIAL NO
GEOLOGICAL SURVEY	SF 080674
UNDRY NOTICES AND REPORTS ON WELLS this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIPÉ NAM

(Do not use this form Use	for proposals to drill or to deepen or plug back to a different reservoir. "APPLICATION FOR PERMIT—" for such proposals.)		
1.		7. UNIT AGREEMENT NAME	
OIL GAS X	OTHER	San Juan 27-4 Unit	
2. NAME OF OPERATOR		8. FARM OR LEASE NAME	
El Paso Natura	l Gas Company	San Juan 27-4 Unit	
3. ADDRESS OF OPERATOR		9. WELL NO.	
Box 990 Farm	61 10. FIELD AND POOL, OR WILDCAT		
See also space 17 below.) At surface	Tapacito Pictured Cliffs E		
20010 250010	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA		
800'S, 1500'E		Sec. 22, T-27-N, R-4-W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE	
	7252 'GT.	Rio Arriba New Mexico	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

				• • •
NOTE	CE OF	INTENTION TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON® CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
(Other)			<u> </u>	Completion of feedominetion resport and hog form,

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) •
- T.D. 4318'. Ran 142 joints 2 7/8", 6.4#, J-55 production casing, 4307' set at 4318 . Baffle set at 4308'. Cemented with 328 cu.ft. cement. 12-14-73 WOC 18 hours. Top of cement at 2250.
- 4-23-74 Tested casing to 4000#-0K. PBTD 4308'. Perf'd 4120-30', 4140-46', 4170-88' with 12 shots per zone. Frac'd with 40,000# 10/20 sand and 40,320 gallons treated water. Dropped 2 sets of 12 balls each. Flushed with 1008 gallons water.



18. I hereby certify that the foregoing is true and correct SIGNED SIGNED	TITLE	Drilling Clerk	DATE 4-25-74
(This space for Federal or State office use)			
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE