Form 9-331 (May 1963)	DEDART	UNITED STATES SUBMIT IN TRIPLICATES DEPARTMENT OF THE INTERIOR (Other instructions on re-				Form approved. Budget Bureau No. 42-R1424.	
		DEPARTMENT OF THE INTERIOR (Other Instructions on re-				5. LEASE DESIGNATION AND SERIAL NO. NM 03560	
		GEOLOGICAL SURVEY				ALLOTTEE OR TRIBE NAME	
	this form for propo	SAND RE AND RE ATION FOR PERMIT-	pen or plug	back to a different reservoir.			
1. OIL GAS	OH. CO CAS CT					MENT NAME	
WELL WE						Lan 28-7 Unit	
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR						an 28-7 Unit	
Box 990,	Box 990, Farmington, New Mexico 8740] LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*					<u> </u>	
ECCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface						POOL, OR WILDCAT CO Pictured Cliffs	
169 5'N	1, 1650'W					ACPA , M., OR BLE. AND OR AREA MT-27-N, R-7-W	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)				M PARISHI 13. STATE	
11. 10		6547°GL			Rio Arriba New Mexic		
16.	Charla A	Pau Ta	1_d:	Natura al Natias Danast an			
		Check Appropriate Box To Indicate Nature of Notice, Report, or					
				[3	QUENT REPORT OF		
TEST WATER SH		PULL OR ALTER CASINO MULTIPLE COMPLETE	,		7	ERING CASING	
SHOOT OR ACIDIZ		ABANDON*	 	SHOOTING OR ACIDIZING		NDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other)			
(Other)				(Note: Report result Completion or Recom	ts of multiple com pletion Report and	pletion on Well Log form.)	
11-10-73	·	rface casing,	held 6	00#/30 minutes.		OFCEIVED	
11-23-73	Pictured Cliffs T.D. 2980'. Ran 99 joints 2 7/8", 6.4#, J-55 production casing, 2970' set at 2980'. Baffle set at 2969 OIL CON. COM. Cemented with 513 cu.ft. cement. WOC 18 hours.						
	Chacra T.D. 4027'. Ran 134 joints 2 7/8", 6.4#, J-55 production casing, 4017' set at 4027'. Baffle set at 4017'. Cemented with 442 cu. ft. cement. WOC 18 hours. Top of cement at 1800'.						
3-22-74	Pictured Cliffs PBTD 2969'. Tested casing to 4000#-OK. Perf'd Pictured Cliffs 2840-48', 2858-68', 2878-88' with 10 shots per zone. Frac'd with 40,000# 10/20 sand, 37,000 gallons treated water. Dropped 2 sets of 10 balls each. Flushed with 710 gallons water.						
	3950-66' v 37,270 ga	Chacra PBTD 4017'. Tested casing to 4000#-OK. Perf'd Chacra 3822-36', 3950-66' with 16 shots per zone. Frac'd with 36,000# 20/40 sand, 37,270 gallons treated water. Dropped 1 set of 16 balls. Flushed with 970 gallons water.					
18. I hereby certify	that the foregoing i	s true and correct					
SIGNED A	J Du	cia .	ritle	Drilling Clerk	DATE	3-26-74	
(This space for I	Federal or State off	ice use)					
		·					
APPROVED BY CONDITIONS OF	F APPROVAL, IF		ritle		DATE _		

*See Instructions on Reverse Side