

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF079527

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1800'N, 800'E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
7174' GL

7. UNIT AGREEMENT NAME
San Juan 27-4 Unit

8. FARM OR LEASE NAME
San Juan 27-4 Unit

9. WELL NO.
82

10. FIELD AND POOL, OR WILDCAT
Tapacito PC Ext

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA
Sec. 26, T-27-N, R-4-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE
Rio Arriba New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

10-04-74 TD 4175'. Ran 134 joints 2 7/8", 6.4#, J-55 production casing, 4163' set at 4175'. Baffle set at 4164'. Cemented with 305 cu. ft. cement. WOC 18 hours. Top of cement at 2750'.

11-08-74 Tested casing to 4000#--OK.
PBTD 4163'. Perf'd 4016-22', 4034-40', 4056-62', 4072-78', 4090-96' with 6 shots per zone. Frac'd with 70,000# 10/20 sand and 67,000 gallons treated water. Dropped 4 sets of 6 balls each. Flushed with 1008 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED A. B. Duce

TITLE Drilling Clerk

DATE November 12, 1974

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side