REPAIR WELL

(Other)

UNITED STATES SUBMIT IN TRIPLICATE® DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

| GEOLOGI | CAI | SHRVFY |
|---------|-----|--------|

| ķ | SF | 0806 | 75 | | | |
|----|----|---------|----------|----|-------|----|
| 5, | IF | INDIAN, | ALLOTTEE | OR | TRIBE | NA |

| 14. PERMIT NO. | 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7261' GL k Appropriate Box To Indicate Nature of Notice, Report, G | 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico | |
|--------------------------------------|--|--|--|
| 940'N, 860'Е | Sec. 34, T27N, R4W | | |
| See also space 17 below.) At surface | Tapacito P.C. Ext. 11. SEC., T., R., M., OR BLK. AND SUBVEY OR AREA | | |
| P. O. Box 990, Far | rmington, New Mexico 87401 Ition clearly and in accordance with any State requirements.* | 92 10. FIELD AND FOOL, OR WILDCAT | |
| 3. ADDRESS OF OPERATOR | 9. WELL NO. | | |
| El Paso Natural Ga | San Juan 27-4 Unit | | |
| WELL WELL OTI | 8. FARM OR LEASE NAME | | |
| OIL GAS X OTI | | San Juan 27-4 Unit | |
| (De not use this form for | proposals to drill or to deepen or plug back to a different reservoir. PLICATION FOR PERMIT—" for such proposals.) | | |

REPAIRING WELL WATER SHUT-OFF TEST WATER SHUT-OFF PULL OR ALTER CASING ALTERING CASING FRACTURE TREATMENT MULTIPLE COMPLETE ABANDONMENT*

FRACTURE TREAT ABANDON* SHOOT OR ACIDIZE CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Test surface casing; held 600#/30 minutes. 5/16/74

Total depth 4255'. Ran 141 joints 2 7/8", 6.4#, J-55 production casing, 4244' set at 4255'. Baffle set at 4245'. Cemented with 226 cubic feet 5/21/74 cement. WOC 18 hours. Top of cement at 3125'.

Test casing to 4000# - OK. P.B.T.D. 4245'. Perf'd 4112-22, 4130-42, 4154-64 6/17/74 and 4174-82' with 10 SPZ. Fraced with 58,000# 10/20 sand and 58,002 gallons treated water. Dropped 3 sets of 10 balls each. Flush with 1050 gallons water.



| | Note 451.3 | |
|--|----------------------|--------------------|
| 8. I hereby certify that the foregoing is true and correct | | |
| 8. I hereby certify that the foregoing is true and correct SIGNED A Succes | TITLE Drilling Clerk | DATE June 18, 1974 |
| (This space for Federal or State office use) | | |
| APPROVED BYCONDITIONS OF APPROVAL, IF ANY: | TITLE | DATE |

*See Instructions on Reverse Side