

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T., R., M

454' FSL, 950' FWL, Sec. 3, T-27-N, R-4-W, NMPM

5. Lease Number

SF-080668

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

San Juan 27-4 Unit

8. Well Name & Number

San Juan 27-4 U #94

9. API Well No.

30-039-20837

10. Field and Pool

Basin Dakota

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☒ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☐ Other -

13. Describe Proposed or Completed Operations

6-23-95 MIRU. SD for weekend.

6-26-95 ND WH. NJ BOP. PT BOP, OK. TOO H w/255 jts 1 1/2" tbg. TIH to 8032'. Plug #1: pump 31 sx Class "B" cmt @ 7624-8032'. TOO H to 5800'. WOC. TIH, tag TOC @ 7614'. TOO H to 6924'. Load hole w/33 bbl wtr. PT csg to 500 psi/5 min, OK. Plug #2: pump 12 sx Class "B" cmt @ 6766-6924' inside csg. TOO H to 5533'. Plug #3: pump 12 sx Class "B" cmt inside csg @ 5375-5533'. TOO H to 4110'. Plug #4: pump 38 sx Class "B" cmt @ 3609-4110'. TOO H to 2400'. SDON.

6-27-95 RU, ran 4 1/2" gauge ring to 3550'. Perf 3 sqz holes @ 3550'. Attempt to establish injection. POOH. Load hole w/6 bbl wtr. Perf 3 sqz holes @ 3450'. POOH. Try to establish injection. (Verbal approval to change plans from Ken Townsend, BLM). TIH to 3604'. Plug #5: pump 41 sx Class "B" cmt inside csg @ 3064-3604'. TOO H. TIH, perf 6 sqz holes @ 1978'. Establish injection. TIH w/4 1/2" cmt retainer, set @ 1928'. Plug #6: pump 26 sx Class "B" cmt outside 7" csg, 15 sx Class "B" cmt in 4 1/2" x 7" annulus @ 1878-1978'. Left 12 sx Class "B" above cmt retainer. TOC @ 1823'. TOO H. Perf 3 sqz holes @ 254'. POOH Establish circ. Plug #7: pump 102 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt out 4 1/2" x 7" annulus. WOC. SDON.

6-28-95 ND BOP. Cut off WH. Pump 4 sx to fill 7" & 9 5/8" csg. Install dry hole marker w/14 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 6-28-95.

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Affairs

Date 6/29/95

(This space for Federal or State Office use)

APPROVED BY

Title

Date

APPROVED

CONDITION OF APPROVAL, if any:

NMOCD