Form	9-331
(May	1963)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR (Other Interior state)

SUBMIT IN TRIPLICATE (Other instructions on re-

Form approved, Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.


SF 0793/63 6. IF INDIAN ALLOTTEE OR TRIBE NAME

GEO	LOGI	CAL	SUR	VEY	

SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)			•
i.		7. UNIT AGREEMENT NA	AME
WELL GAS WELL OTHER		San Juan 28-6	Unit
2. NAME OF OPERATOR		8. FARM OR LEASE NA	ME
El Paso Natural Gas Company		San Juan 28-6 Unit	
3. ADDRESS OF OPERATOR		9. WELL NO.	
PO Box 990, Farmington, NM 87401		206	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface 1925'N, 1190'E		10. FIELD AND POOL, OR WILDCAT	
		Basin Dakota 11. SEC., T., R., M., OR BLK. AND SUBVEY OR AREA	
			·
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
	6281'GL	Rio Arriba	New Mexico
16. Check A	Appropriate Box To Indicate Nature of Notice, Report, o	Other Data	

SUBSEQUENT REPORT OF:
WATER SHUT-OFF  FRACTURE TREATMENT  SHOOTING OR ACIDIZING  (Other)  (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*
  - 5-9-74 TD 3219'. Ran 101 joints 7", 20#, J-55 intermediate casing, 3205' set at 3219'. Cemented with 218 cu.ft. cement. WOC 12 hours, held 1200#/30 min. Top of cement at 2900'.
  - TD 7503'. Ran 232 joints 4 1/2", 10.5# and 11.6#, J-55 production casing. 5-18-74 7493' set at 7503'. Float collar set at 7488'. Cemented with 657 cu.ft. cement. WOC 18 hours, top of cement at 2500'.
  - 5-25-74 PBTD 7488'. Tested casing to 4000#-OK. Perf'd 7254', 7272', 7356', 7370', 7432', 7448', 7462', with 1 shot per zone. Frac'd with 70,000# 40/60 sand and 76,500 gallons treated water. No ball drops. Flushed with 5020 gallons water.



DURANCO, COLO.

18. I hereby certify that the foregoing is true and correct		
SIGNED M. M. Augus	TITLE Drilling Clerk	May 29, 1974
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE