

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 990, FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE***915'S, 1180'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☒
FRACTURE TREAT ☐	☒
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

5. LEASE
SF 080674
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
San Juan 27-4 Unit
8. FARM OR LEASE NAME
San Juan 27-4 Unit
9. WELL NO.
99
10. FIELD OR WILDCAT NAME
BLANCO MESA VERDE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 16, T-27-N, R-4-W
NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7274' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/5/78: T.D. 4429'. Ran 111 joints 7", 25 & 20#, N-80 & K-55 intermediate casing, 4417' set at 4429'. Cemented with 202 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 3550'.

8/8/78: T.D. 6761'. Ran 57 joints 4 1/2", 10.5#, K-55 casing liner, 2494' set 4267-6761'. Float collar set at 6744'. Cemented with 431 cu. ft. cement. WOC 18 hours.

8/17/78: PBTD 6744'. Tested casing to 3500#, OK. Perfed C.H. and Men. 5842, 5856, 5865, 5876, 5906, 5916, 5934, 5959, 5972, 5978, 6083, 6130, 6156, 6168 w/1 SPZ. Fraced with 45,000# 20/40 sand and 75,500 gallons water. Flushed with 8500 gal. water. (OVER)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. D. [Signature] TITLE Drilling Clerk DATE 8/21/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

SEP 1 1978

U.S. GEOLOGICAL SURVEY

Instructions

1. This form is to be used for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands. It is to be filled out by the operator, and if approved or accepted by the State, on all lands in such State, pursuant to applicable State law and Federal law. If there are any special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, or State, or regional offices, they are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

2. If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local office for Federal outline for specific instructions.

3. If a proposal to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, each proposal and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid content; and sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of putting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well was abandoned for an inspection looking to approval of the abandonment.

Perforated Mass. and Lower P.L. 6521, 6527, 6532, 6537, 6542, 6550, 6554, 6567, 6574, 6586, 6593, 6405, 6412, 6434, 6440, 6453, 6485, 6537, 6550, 6580, 6638, 6662, 6684 w/1 SPZ. Traced with 40,000# 20/40 sand and 110,000 gallons water. Flushed with 8900 gal. water.

GPO : 1975 O - 214-143