

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		San Juan 27-4 Unit
3. ADDRESS OF OPERATOR		8. FARM OR LEASE NAME
Box 990, Farmington, New Mexico 87401		San Juan 27-4 Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		9. WELL NO.
2210' S, 2340' W		86
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		Tapacito Pictured Cliffs Ext
7117' GL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
		Sec. 27, T-27-N, R-4-W
		N.M.P.M.
		12. COUNTY OR PARISH
		13. STATE
		Rio Arriba New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☒
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-7-74: Tested surface casing; held 600#/30 minutes.

6-12-74: T. D. 4118'. Ran 131 joints 2 7/8", 6.4#, J-55 production casing, 4107' set at 4118'. Baffle set at 4107'. Cemented with 237 cu. ft. cement. WOC 18 hours. Top of cement at 2700'.

7-29-74: Tested casing to 4000#, O.K.
P. B. T. D. 4107'. Perfed 4008, 4009, 4013, 4014, 4030, 4031, 4032, 4033, 4056, 4057' with 1 SPF. Fraced with 60,000# 20/40 sand and 55,200 gallons foam. Dropped 1 set of 5 balls. Flushed with 1000 gallons foam.



18. I hereby certify that the foregoing is true and correct

SIGNED

Gregory M. [Signature]

TITLE

Drilling Clerk

DATE

July 31, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

sr