

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
*SEE INSTRUCTIONS ON REVERSE SIDE

Form 9-74
Bureau Order No. 10 R1171

5. LEASE DESIGNATION AND SERIAL NO.

SE079365

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a different reservoir.
Use "APPLICATION FOR PERMIT—" for such purposes.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

1450'S, 1180'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6478' GL

7. UNIT AGREEMENT NAME

San Juan 28-6 Unit

8. FARM OR LEASE NAME

San Juan 28-6 Unit

9. WELL NO.

197

10. FIELD AND POOL, OR WILDCAT

South Blanco PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 14, T-27-N, R-6-W

N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-30-74 TD 3285'. Ran 104 joints 2 7/8", 6.4#, J-55 production casing, 3275'. set at 3285'. Baffle set at 3275'. Cemented with 276 cu. ft. cement. WOC 18 hours. Top of cement at 1850'.

11-25-74 Tested casing to 4000#--OK.
PBSD 3275'. Perf'd 3200-06', 3218-24', 3240-46' with 6 shots per zone.
Frac'd with 42,966# 10/20 sand and 42,966 gallons treated water. Dropped 2 sets of 6 balls each. Flushed with 756 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Dimeo

TITLE Drilling Clerk

DATE November 26, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

21