DEPUTY O'L & GAS INSOLUTOR

Meter Number:90290
CAS NO Recation Name:SAN JUAN 28-7 UNIT #217

DEC 2 9 1997

Location:TN-27 RG-07 SC-28 UL-B 2 - Federal NMOCD Zone:OUTSIDE Hazard Ranking Score:00

RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone 10^{-9} to 10^{-13} cm/sec Shale 10^{-12} to 10^{-16} cm/sec Clay 10^{-12} to 10^{-15} cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.

EPFS

FIELD PIT SITE ASSESSMENT FORM

GENERAL	Meter: 90290 Location: San Juan 28-7 Unit 217 Operator #: 0203 Operator Name: America P/L District: Blanco Coordinates: Letter: B Section 28 Township: 27 Range: 7 Or Latitude Longitude Pit Type: Dehydrator Location Drip: Line Drip: Other: Site Assessment Date: 6/8/44 Area: 03 Run: 6/							
SITE ASSESSMENT	NMOCD Zone: (From NMOCD Maps) Inside Outside (I) Fee (3) Outside Indian Depth to Groundwater Less Than 50 Feet (20 points) Greater Than 100 Ft (0 points) Wellhead Protection Area: Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) Cgreater Than 1000 Ft (10 points) (3) Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) (3) Name of Surface Water Body (Surface Water Body (Surface Water Body: Perennial Rivers, Major Wash, Streams, Creeks, Irrigation Canals, Ditches, Lakes, Ponds) Distance to Nearest Ephemeral Stream (1) < 100'(Navajo Pits Only) (2) > 100' TOTAL HAZARD RANKING SCORE: D POINTS							
RKS	Remarks: Relline + Vuln - Durcile							
REMARKS	3pits. Clase 1. Pit has liquidinit. (Called Blunco Office)							
RE	りなれずい							

	ORIGINAL PIT LOCAT	ION
179	Original Pit : a) Degre e s from North <u>172° 1</u> b) Length : <u>50′</u> Width : <u>-</u>	
ORIGINAL PIT LOCATION	17. 20' 35' 50'), a
REMARKS	Remarks: fictures@0927(1-5) rollb End Dump	
	Fenced + Berned area of pit is 50' x35'. Actua	1 p1+ 17 32 X30 X4,
	Completed By:	
	Cong Clane	6/8/94
i	• · · · · · · · · · · · · · · · · · · ·	

FIELD PIT REMEDIATION/CLOSURE FORM

GENERAL	Meter: 90290Location: Say Joen 28-7 Val 21> Coordinates: Letter: 3 Section 38 Township: 27 Range: 7 Or Latitude Longitude Date Started: 9-6-94 Run: 03 61
FIELD OBSERVATIONS	Sample Number(s): VW246 Sample Depth:12' Feet Final PID Reading792
CLOSURE	Remediation Method: Excavation
	Envirotech
REMARKS	Remarks: P.t real wet.
	Signature of Specialist: Wiley (SP3181) 93/16/94



FIELD SERVICES LABORATORY ANALYTICAL REPORT

PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

	SAMPLE	IDENTIFICA	TION			
	Field	I ID		Lab ID		
SAMPLE NUMBER:	SAMPLE NUMBER:			946058		
MTR CODE SITE NAME:	90290		N/A パクロ			
SAMPLE DATE TIME (Hrs):						
SAMPLED BY:	N/A					
DATE OF TPH EXT. ANAL.:	DATE OF TPH EXT. ANAL.: 9/8/94			9/8/94		
DATE OF BTEX EXT. ANAL.:	N/A		BLACK SAUD & CLAY			
TYPE DESCRIPTION:	16		BLACK			
REMARKS:						
		RESULTS				
PARAMETER	RESULT	UNITS		QUALIF		V(=)
			DF	<u> </u>	M(g)	V(ml)
TPH (418.1)	7340	MG/KG			1,27	28
HEADSPACE PID	792	PPM				
PERCENT SOLIDS	87.3	%				# ₁ ,
	<u> </u>	TFH is by EPA Metho	od 418.1			
Narrative:						
DF = Dilution Factor Used						
Approved By:			Date:	9/30/44		

> Perkin-Elmer Model 1600 FT-IR Analysis Report

94/09/08 15:37

Sample identification 946058

Initial mass of sample, g

Volume of sample after extraction, wl

Fetroleum hydrocarbons, ppm 7339.536 Net absorbance of hydrocarbons (2930 cm-1) 0.588

