STATE OF NEW MEXICO ENERGY and MINERALS

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

DEPARTMENT
This form is not to
be used for reporting
packer leakage tests
in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

								Well	
Operator	MERIDIAN OIL INC.	Lease	SAN JUAN 27-4	I JUAN 27-4 UNIT		No.	121		
Location									
of Well:	Unit A Sect	t 18 Twp.	27 N	Rge.	4W	County		RIO ARRIE	BA
	NAME OF RI	ESERVOIR OR POOL		TY	PE OF PROD.	METHO	OD OF PROD.	PROD.	MEDIUM
				 '	(Oil or Gas)	(Flo	ow or Art. Lift)	(Tbg. o	or Csg.)
Upper							!		
Completion	PICTURED CLIFFS		GAS	↓	FLOW	T	BG		
Lower				-			1		
Completion	MESAVERDE		GAS		FLOW		TBG		
.	т	PRE-J	FLOW SHUT	-IN PRE	SSURE DATA		т		
Upper	Hour, date shut-in	Length of time shut-in		SI press			Stabilized? (Yes	s or No)	!
Completion	4-7-95	6 DAY	S		489		ļ		
Lower]								!
Completion	4-7-95	4 DAY			508				
			FLOW TEST	. NO. 1	T			· ONED	
	1	t (hour,date)* 4-11-95					or Lower)	LOWER	
TIME	LAPSED TIME	PRESS	T		PROD. ZONE				1
(hour.date)	SINCE*	Upper Completion	Lower Compi	letion	TEMP	├──	REMARI	KS	
9-Apr		488	50	7	,				
10-Apr		489	50	17					
11-Apr		489	50	18					
· · · ·		1			 				
12-Apr	ļ	489	38	0		<u> </u>			
13-Apr		490	37	8					
Production r	rate during test				<u> </u>				
Oil:	BOPD based on	Bbls.	in	_ Hours	•	_Grav.		GOR _	<u>_</u>
Gas:		_MCFPD; Tested thr	ru (Orifice or	Meter):					
		MID-	TEST SHUT	-IN PRE	SSURE DATA				
Upper	Hour, date shut-in	Length of time shut-in		SI pres.		Stabilized? (Yes or No)			
Completion					Porb	(100 01 110)			
Lower	Hour, date shut-in	Length of time shut-in		SI press	s. psig	•	Stabilized? (Yes	e or No)	
Completion				J. 7	bare		Jun 1111	, 01 1.0,	

(Continue on reverse side)

ELOW TEST NO 3

			I LOW (ES	1 NO. 2			
Commenced :	at (hour,date)**			Zone producing (Up)	per or Lower):		
ПМЕ	LAPSED TIME	PRESSURE		PROD. ZONE			
(hour,date)	SINCE**	Upper Completion	Lower Completion	TEMP.	l F	REMARKS	
1							
!							
1							
	<u> </u>						
						-	
				_1.			
Production	rate during test						
Oil:	BOPD based on				Grav.	GOR	
Gas:		MCFPD; Te	ested thru (Orifice or	Meter):			
Remarks:			·			·	
							
I hereby cer	rtify that the inform	ation herein containe	d is true and comple	te to the best of my k	nowledge.		
	ah	my Rolins	4				
Approved		nny Rolins	-19	Operator	Meridian Oi	I Inc.	
M M							
New Mex	cico Oil Conservatio	1497 1995	5	Ву	Tanya Atcit	ty	
Bv					0 1:	A	
рŅ	DEPLIT	Y OIL & GAS INSP	ECTOR	Title	Operations	Associate	
Title		. 5.2 % 6/10 /10/	20.01	_	0.5.05		
i ille				Date	6-5-95		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within seven days after except that the previously produced zone shall remain shut-in while the zone which actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be connected on all multiple completions within seven days following recompletion and/or chemical or frac-ture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization, both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packer Leakage Test form Revised 10/01/78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).