

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87041

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1150'N, 1725'E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
RECEIVED
MAY 21 1980
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
SF 080675

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 27-4 Unit

8. FARM OR LEASE NAME
San Juan 27-4 Unit

9. WELL NO.
132 (MD)

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 27, T-27-N, R-4-W
N.M.P.M.

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7229' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 5-17-80: PBDT 8542' Tested Casing to 4500#, OK. Perfed Dakota 8302,8307,8312,8393, 8400,8423,8427,8431,8436,8442,8448,8465,8470,8477,8498,8500,8528,8530' W/1 SPZ. Fraced w/ 147,500# 20/40 sand & 90,000 10/20 sand, & 110,000 gal. wtr. Flushed w/ 18,850 gal. wtr.
- 5-18-80: Perfed Lower P.L. 6471,6487,6509,6516,6528,6570,6578,6638' W/1 SPZ. Fraced w/21,500# 20/40 sand, 43,000 gal. wtr. Flushed w/17,390 gal. wtr. Perfed Massive P.L. 6274,2678,6300,6305,6310,6321,6327,6332,6338, 6343,6356,6362, 6367,6387,6401,6415' W/1 SPZ. Fraced w/ 44,500# 20/40 sand, 89,000 gal. wtr. Flushed w/ 89,000 Gal. wtr.
- 5-19-80: Perfed C.H. & Men. 5788,5800,5805,5837,5858,5883,5888,5902,5910,5915,5921' W/1 SPZ. Fraced w/21,500# 20/40 sand, 43,000 gal. wtr. Flushed w/ 16,250 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. P. Quiso TITLE Drilling Clerk DATE May 21, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 27 1980

*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY McL Kuchera