REPAIR WELL

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on response side) Budget Bureau No. 42 R142 5. Lease designation and serial no

SUBMIT IN TRIPLICATES.

Budget Bureau No. 42 R142

	The state of the s
i	SF 080669
	SP 000000

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTRE OR TRIBE NAME
	7. UNIT AGREEMENT NAME
WELL GAS WELL OTHER	San Juan 27-4 Unit
NAME OF OPERATOR	8, FARM OR LEASE NAME
El Paso Natural Gas Company	San Juan 27-4 Unit
. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Box 990, Farmington, New Mexico 87401 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1500'N, 1450'E	10.5 (PM) 10. FIELD AND FOOL, OR WILDCAT TAPACITO PC Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR ABEA Sec. 19, T-27-N, R-4-W N.M.P.M.
4. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
6833 ' GL	Rio Arriba New Mexic
6. Check Appropriate Box To Indicate Nature of Notice, Report, or	Other Data
NOTICE OF INTENTION TO: SUBSE	QUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING	X REPAIRING WELL, ALTERING CASING ABANDONMENT*

- (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - TD 4044'. Ran 104 joints 7", 20 & 23#, KS intermediate casing, 4032' set at 4044'. Cemented with 222 cu. ft. cement. WOC 12 hours, held 1200#/30 Top of cement at 2600'. minutes.
 - TD 6348'. Ran 78 joints 4 1/2", 10.5#, KS casing liner, 2465' set 3883-6348'. 07-08-76 Float collar set at 6331'. Cemented with 435 cu. ft. cement. WOC 18 hours.
 - PBTD 6331'. Tested casing to 4000#, OK. Perf'd PC 3715', 3747', 3751', 09-10-76 3758', 3762', 3774', 3787', 3794' with 1 shot per zone. Frac'd with 56,000# 10/20 sand and 55,440 gallons water. No ball sets dropped. Flushed with 6678 gallons water. Perf'd MV 5396', 5460', 5494', 5513', 5518', 5535', 5873', 5879', 5899', 5905', 5912', 5950', 5959', 5967', 6007', 6021', 6097', 6119', 6205', 6239' with 1 shot per zone. Frac'd with 55,000#--20/40 sand and 57,540 gallons water. No ball sets dropped. Flushed with 8400 gallons water.

18. I hereby certify that the foregoing is true a	nd condicto i in a come	
SIGNED 21 L. Luc	Of Courts Drilling Clerk	DATE September 13,19
(This space for Federal or State office use)	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
APPROVED BY	· TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	, •	