Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT BUREAU OF LAND MANAGEMENT



FORM APPROVED

Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. LEASE DESIGNATION AND SERIAL NO.

		SF 078640
SUNDRY NOTICES AND REPORTS ON WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		• • •
Use "APPLICATION FOR PERM	IIT-" for such proposals	
SUBMIT IN TRIPLICATE		7. IF UNIT OR CA, AGREEMENT DESIGNATION
		SAN JUAN 28-7
1. TYPE OF WELL		8. WELL NAME AND NO.
OIL WELL GAS WELL OTHER 2. NAME OF OPERATOR		#210
	OCT 2000	9. API WELL NO.
CONOCO INC. 3. ADDRESS AND TELEPHONE NO.		30-039-21018
P.O. Box 2197, DU 3066, Houston, TX 772	52 2107 2 (224) 500 4040	10. FIELD AND POOL, OR EXPLORATORY AREA
4. LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Des	52-2197 (281) 293-1613	OTERO CHACRA
1800' FNL & 950' FWL, Section 21, 1		11. COUNTY OR PARISH, STATE
12. CHECK APPROPRIATE BOX(s)	TO INDICATE MATURE OF NOTICE	RIO ARRIBA COUNTY
	TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE	OF ACTION
Notice of Intent	Abandonment	Change of Plans
Subsequent Report	Recompletion	
Subsequent Report	Plugging Back	New Construction
Final Abandonment Notice		Non-Routine Fracturing
	Casing Repair	Water Shut-Off
	Altering Casing	Conversion to Injection
	Other: RECOMPLETE PC	Dispose Water (Note: Report results of multiple completion on Well Completion or
 Describe Proposed or Completed Operations (Clearly state all p directionally drilled, give subsurface locations and measured and 	ertinent details, and give pertinent dates, including estin I true vertical depths for all markers and zones pertinen	nated date of starting any proposed work. If well is it to this work.)
SEE ATTACHED SU	JMMARY FOR RECOMPLETIO	N DETAILS.
I hereby certify that the foregoing is true and correct		
SIGNED THE STATE (This space for Federal or State office use)	TITLE DEBRA SITTNER, As Age	nt for Conoco Inc. DATE 9/5/00
APPROVED BY Conditions of approval, if any:	TITLE	DATE
itle 18 U.S.C. Section 1001, makes it a crime for any persor ctitious or fraudulent statements or representations as to an	y matter within its jurisdiction.	nent or agency of the Unites States any false,
	* See Instruction on Reverse Side	ACCEPTED FOR RECORL

OCT 1 3 2000

FARMINGTON FIELD OFFICE

CONOCO INC. **SAN JUAN 28-7 #210**

API # 30-039-21018 SEC 21 - T27N - R07W UNIT LETTER "E" 1800' FNL - 950' FWL

- 8/7/00 350 psi casing. Safety meeting. MIRU, blow well down. ND tree NU companion flange, spacer spool, and BOP. Secure well for night.
- 8/8/00 0 psi casing. Safety meeting. RU Blue Jet. RIH with wireline guage ring to 3830'. No tight spots noted. PU 2-7/8' CIBP and set over Chacra at a depth of 3815'. POOH, RU bailer. RIH with dump bailer and dump 20' cement on top of plug. (TOC at 3795') POOH. Test plug to 500 psi. Plug held for 15 minutes. PU logging tools. RIH and CBL from 3500' to 2500'. POOH, RU stinger isolation tool. Pressure test casing to 3500 psi. Casing held solid for 15 minutes. RD stinger. RI hole with Blue Jet 2" go-winder guns and perforate PC with 158 holes as follows. 2984' to 2946' 2 JSPF, 2943' to 2902' 2 JSPF. RD Blue Jet. Secure well for night.
- 8/9/00 Stand by wait for BJ Services.
- 8/10/00 Stand by wait for BJ Services.
- 0 psi casing. Safety meeting. RU BJ Services, pre job safety meeting. Test lines to 4500 psi. Set POP off at 3450 psi. Break down with 1% KCL, broke at 1500 psi. ISDP of 480 psi. ST 15% HCL spear head, pump 1500 gal at 8.5 BPM average rate and 1450 average psi. Frac PC with 103,880# 20/40 brady sand, and 47,544 gal 70Q linear foam with average DH rate of 28 BPM and average psi of 3000#. ISDP of 1580 psi. 5 minutes 1028#, 10 minutes 1008#, 15 minutes, 998#. RD BJ Services, RU flow back lines. RD stinger isolation tool. Post job meeting. ST flowing well back on ¼" choke at 840#. Flow for 2 hours and swap to ½" choke at 580#. 17:00 hours 160 psi flowing no sand, no oil, and moderate water. All nitrogen not to surface. Turn over to dry watch. 20:00 hours 60# on ½" choke. Moderate water, no sand, no oil. 24:00 hours 60# on ½" choke. Moderate water, no sand, no oil.
- 8/12/00 All pressure readings are taken with 2" line and a ½" choke. As of 24:00 hours on 8/11/00, recovered 18 bbls water, with no traces of oil. 4:00 a.m. 40#, still flowing water, no oil, heavy sand. 8:00 a.m. 50#, light water, heavy sand, no oil. 12:00 a.m. 50#, light water, moderate sand, no oil. Sand cut out nipple, shut well in to change out nipple. Returned to flowing well after 15 minutes. 16:00 p.m. 50#, light water, heavy to moderate sand, no oil. Shut in to change out another nipple on flow line. Returned to flowing in 15 minutes. 20:00 p.m., 40#, very light water, moderate sand, no oil. 24:00 p.m., 50#, light water, moderate sand, no oil. Daily fluid recovered was approximately 10 bbls. TOT fluid recovered thus far is 28 bbls.
- 8/13/00 TOT. Fluid recovered as of midnight 8/12/00 was 28 bbls. 8/13/00, 4:00 a.m., 40#, very little water, light sand, no oil. 8:00 a.m., 40#, no water, light sand, no oil. Shut in well to replace bull plug. Returned to flow in 10 minutes. 12:00 a.m., 45#, light sand, no water or oil. 16:00 p.m., 45#, light sand, no water or oil. 20:00 p.m., 45#, flowing sand and gas. 24:00, 45#, flowing sand and gas, no water or oil.
- 8/14/00 Well still flowing with an average pressure of 47#, with very little water, light to moderate sand, no oil. TOT. Fluid recovered is approximately 40 bbls. Sand on bottom of tank makes it hard to guage. Midnight, 50#, moderate sand, light water, no oil.

CONOCO INC. **SAN JUAN 28-7 #210**

API # 30-039-21018

SEC 21 - T27N - R07W UNIT LETTER "E" 1800' FNL - 950' FWL

- 8/15/00 Release dry watch at 8:00 a.m. Safety meeting. Pump 15 bbls water to kill well. RU 1-1/4" tools, PU 2-1/4" blade bit and RIH with 97 joints and tagged fill at 2959'. RU BJ Services and clean out with N2 to depth of 3756'. Pump 5 bbls foamed sweap, pump till pottoms up and blow add 15 minutes. POOH with 20 stands standing back to get above perfs. Secure well for night.
- 8/16/00 550 psi on casing. Safety meeting. Pump 10 bbls water to kill well. POOH with 1-1/4' drill string and lay down. Came out of hole short 6 joints pipe, bit sub and bit. Call for over shot. PU Halliburton 2-7/8" RBP, RIH and set at 993'. TOOH standing back. Load hole with water RD BOP and recompletion spool. Removed 10 RD nipple from casing hanger. RU spool and BOP. RIH with drill string and retrieve RBP. POOH and laydown Halliburton RBP. Secure well for night.
- 8/17/00 525# casing. Safety meeting. PU Weahterford overshot, and RIH to tag fish. Latch onto fish with overshot. POOH and laydown 6 joints 1-1/4" drill pipe and bit. RIH with drill string. TOOH laying down singles. Pump 7 bbls water to kill well. ND BOP and recompletion spool. Companion flange was stuck on casing head. Cannot break apart with current tools. RU nipple and master valve. Secure well for night. Will try to break companion flange off with longer cheater pipes in the a.m.
- 8/18/00 475 psi. Safety meeting. Final Report. Work on flange until it breaks loose. Pump 10 bbls water to kill well. RD master valve, removed companion flange. Install casing. Head nut. RU master valve. Well came around and started flowing to laydown tank. Let well flow until all fluid unloads. Call for roustabouts to install plunger equipment and seperator. RD move off location. Turn well over to operator and sales. Final test results: Well is 2-7/8" slim hole, and no tubing will be installed. 250 mcfd with no oil and no water. Witnessed by Mike Stone with L&R. Test was taken flowing up casing with 47# on a ½" choke.