## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wel	ls
1. Type of Well GAS	5. Lease Number Jic Cont 95 6. If Indian, All. or Tribe Name Jicarilla Apache 7. Unit Agreement Name
2. Name of Operator MERIDIAN OIL	8. Well Name & Number
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	Jicarilla 95 #4A
4. Location of Well, Footage, Sec., T, R, M 990'FNL 990'FWL Sec.26, T-27-N, R-3-W, NMPM	10. Field and Pool Gavilan PC/ Blanco MV 11. County and State Rio Arriba Co, NM
Casing Repair	<pre>tion Change of Plans New Construction     Non-Routine Fracturing</pre>
The Pictured Cliffs will be perforated and stimulated in the following manner:  perfs. Run CBL to verify TOC. If good top is not seen at least 5 cmt work will be performed. The PC will be perfd 3858-4090" ar fracture stimulated. Run after frac GR log to verify if frac stayed Application is being made to NMOCD for commingling. Attache	0' above proposed top PC perf, remedia nd stimulate w/approx 1500 gal acid and d in zone. TIH w/2 3/8" tbg landed @ 630
14. I hereby certify that the foregoing is true and of Signed	
(This space for Federal or State Office use) APPROVED BY CONDITION OF APPROVAL, if any:  Many	Circ Date 2/16/9

# NEW MEXICO OIL CONSERVATION COMMISSION. WELL LOCATION AND ACREAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section. Well No. Operator Jicarilla 95 Meridian Oil Inc. Range Township Unit Letter Rio Arriba 27N 26 Actual Footage Location of Well: West 990 North feet from the feet from the line and Dedicated Acreage: Pool Ground Level Elev: Producing Formation 320/160 Blanco /Gavilan , Mesaverde /Pic.Cliffs 7308 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation . Yes ... No If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commis-CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. Found Staridard GLO Corners Peggy Bradfield Regulatory Representative R 3 W 27 N Meridian Oil Inc. I hemby certify that the well location notes of actual surveys made by me or ler my supervision, and that the same true and correct to the knowledge and belief. Date Surveyed 1976 Registered Professional Enginee and/or Land Surveyor

#### **JICARILLA 95 #4A**

Unit D, Section 26, T27N, R03W Recommended Recompletion Procedure Pictured Cliffs Pay Add & Completion

Note: Notify BLM (761-8762) and NMOCD (334-6178) 24 hours prior to rig activity.

Inspect location and install and/or test rig anchors. Install 1 - 400 bbl rig tank and fill w/ 2% KCl water. Approximately 205 jts. 2-3/8" 4.7# J-55 tubing will be required (MOI, District Tools) for cleanout and production. Comply with all BLM, NMOCD, Jicarilla Apache, and MOI rules and regulations. Notify engineering when work has commenced. Hold Safety Meetings on a regular basis.

1. Install 1 X 400 bbl frac tanks and fill with 2% KCl water.

- 2. Hold Safety Meeting. MIRU. Place fire and safety equipment in easily accessible locations. NU relief line and blooie line to laydown flow tank. Obtain and record all wellhead pressures.
- 3. Blow down tubing. If tubing will not blow down, kill well with KCl water. PBTD is 6365'.
- 4. TOOH with 5765' of 2-3/8" 4.70# tubing, visually inspect and tally tubing.
- 5. RU wireline. RIH with 4-1/2" 10.5# guage ring and check pipe. PU Baker Model G Retrievable bridge plug, TIH and set bridge plug at 4180'. Run GR CBL CCL in 4-1/2 casing from bridge plug to Surface pipe. (Cmt circ. stg1, TOC @ 550' (TS), stg 2). TOC must be above 3800' to continue. Evaluate GR CBL CCL and send copy to production engineering.
- 6. TIH w/ treesaver. Pressure test treesaver and casing to 3200 psi. for 15 min. If pressure test fails, prepare to test and repair casing. Contact Production Engineering and a casing repair will be submitted. TOOH with treesaver.

#### Pictured Cliffs Stimulation:

7. Select-Fire Perf. the following intervals w/ 3-1/8" HSC -3125-306, 12 gram Owen charges 0.31" holes w/ 12.02 " penetration:

3858' - 4090'. (22 Holes)

- 8. RD wireline. TIH w/ treesaver.
- 9. RU stimulation company. Hold Safety Meeting. Pressure test surface treating lines to 5000 psi. Maximum STP during acid job is 3200 psi. Pump 1,500 gals 15% HCl w/additives at a rate of 4-6 BPM, attempt to ball-out the perforations. Drop a total of 33 7/8" RCN ball sealers (1.3sp.gr.) spaced evenly throughout the job. Record rates and pressures while attempting to achieve ball-out.
- 10. RD stimulation company. TOOH w/ treesaver. RU wireline, run junk basket to knock-off/retrieve as many ballsealers as possible. TIH w/ treesaver. RU stimulation company. Prepare to fracture stimulate the Pictured Cliffs.
- 11. Pressure test surface treating lines to 5000 psi. Maximum treating pressure is 3200 psi. Fracture and tag the PC according to the attached procedure. Flow-back the well immediately using a variable choke manifold. Increase choke size as needed to keep the well from logging off, if possible. When pressures and flow rates allow, TOOH w/ treesaver.

### Jicarilla 95 #4A Pictured Cliffs Pay-Add

- 12. TIH w/ retreieving head and 2-3/8" 4.70# workstring and clean out to the retrievable bridge plug @ 4180' with air until sand production is minimal. Obtain pitot gauge for the Pictured Cliffs formation. Record pitot gauge as the Pictured Cliffs formation only. Latch onto the retrievable bridge plug and TOOH.
- 13. RU wireline, run After-frac Tracer Survey-GammaRay (report if frac stayed in zone, if possible), POOH. RD wireline. Send copy of logs to Production Engineering.
- 14. TIH w/ one joint 2-3/8" 4.7# J-55 tubing, seating nipple, and 2-3/8" production tubing. Cleanout to 6365' with air. Land tubing @ +/-6300' (65' of rathole) and obtain final pitot gauge. ND BOP, NU WH. Contact Production Operations for well tie-in. RD and MOL.

		Approved:	
			Drilling Superintendent
Suggested Vendors:			
Wireline:	Petro Wireline	326-6669	
Radioactive Tag:	ProTechnics, Intl	326-7133	
Tubing:	MOI, District Tools	326-9826	
Stimulation:	WCNA	327-6222	
Treesaver:	WIT	599-5609	
Production Oper.:	Bruce Voiles	326-9571	
Engineering:	Brian Ault	326-9871 w	
<b>5</b>		326-6613 h	

#### Jicarilla 95 #4A

Unit D, Sec. 26, T27N, R3W

#### Pictured Cliffs Pay Add and Stimulation

