

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐

2. NAME OF OPERATOR

Palmer Oil and Gas Company

3. ADDRESS OF OPERATOR

Box 2564 Billings, Montana 59103

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

285' FSL, 800' FWL
AT SURFACE: 1070'
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) ☐

5. LEASE

Joint Venture Agreement

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Apache-JVA

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Jicarilla Apache Prospect

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 30, T27N, R2W

12. COUNTY OR PARISH

Rio Arriba

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6195' GR 7206' gl

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well failed to produce gas in commercial quantities from either the Mesaverde or the Pictured Cliffs: We propose to permanently abandon the well as soon as you concur with our procedure:

1. Move in and rig up pulling unit. Hole is full of Mesaverde and Pictured Cliff water.
2. Set cast iron bridge plug at 5575' and dump 10 sx. cement on top of it. Mesaverde perms are from 5596' to 6096'.
3. Run tubing to 3800' and spot 60 sx. cement plug across Pictured Cliffs perms (3639'-3787').
4. Spot 25 sx. cement plug at surface.
5. 4 1/2" casing will be left in place as it is cemented from TD to surface. Install dry hole plug. Reseed location.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED

Harold W. Elledge

TITLE Consultant

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

