

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
**Palmer Oil and Gas Company**

3. ADDRESS OF OPERATOR  
**Box 2564 Billings, Montana 59103**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: **985 FSL, 800' FWL**  
AT TOP PROD. INTERVAL: **Same as above**  
AT TOTAL DEPTH: **Same as above**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
**Joint Venture Agreement**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
**Apache**

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
**Apache - JVA**

9. WELL NO.

**1**

10. FIELD OR WILDCAT NAME

**Vicarilla Apache Prospect**

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

**Sec. 30, 27N, 2W**

12. COUNTY OR PARISH

**San Arriba**

13. STATE

**New Mexico**

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
**7206 CL**

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We plan to plug and abandon this well as follows:

Plug 1 5525'-5725' across top of Mesaverde perforations.  
Plug 2 3375'-3825' across Pictured Cliffs perforations.  
Plug 3 3150'-3350' across the Ojo Alamo.  
Plug 4 25 sacks at surface with appropriate marker.

The location will be cleaned up, rehabilitated, and reseeded.  
Cement is presently circulated from TD to surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED **Harold W. Eledge**

TITLE **Consultant**

DATE **May 31, 1978**

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

**RECEIVED**

**JUN 2 1978**

**U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.**

\*See Instructions on Reverse Side