

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.
SF079527

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME San Juan 27-4 Unit	
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME San Juan 27-4 Unit	
3. ADDRESS OF OPERATOR P. O. Box 990, Farmington, NM 87401		9. WELL NO. 135	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1030'N, 1660' E		10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 36, T-27-N, R-4-W N.M.P.M.	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7243' GL		12. COUNTY OR PARISH Rio Arriba	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07-14-77 T.D. 4399'. Ran 107 joints 7", 20#, K-55 intermediate casing, 4387' set at 4399'. Cemented with 249 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 4050'.

07-19-77 T.D. 6595'. Ran 57 joints 4 1/2", 10.5#, K-55 casing liner, 2354' set 4241-6595'. Float collar set at 6578'. Cemented with 403 cu. ft. cement. WOC 18 hours.

08-04-77 P.B.T.D. 6578'. Tested casing to 4000#, OK. Perfed 5841', 5865', 5878', 5885', 5892', 5906', 5974', 5980', 5986', 6005', 6014', 6084', 6096', 6124' with 1 shot per zone. Fraced with 45,000#--20/40 sand and 45,000 gallons water. Flushed with 8274 gallons water. Perfed 6225', 6231', 6237', 6243', 6283', 6290', 6306', 6314', 6322', 6331', 6358', 6373', 6383', 6421', 6439', 6455', 6483' with 1 shot per zone. Fraced with 50,000#--20/40 sand and 55,250 gallons water. Flushed with 8526 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

A. D. Dices

TITLE

Drilling Clerk

DATE

August 5, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side