

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Consolidated Oil & Gas, Inc.
3. ADDRESS OF OPERATOR
1860 Lincoln Street, Denver, Colo 80295
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- | | | |
|-----------------------|--------------------------|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Case & Cement | | |

5. LEASE
SF 079527A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Champlin
9. WELL NO.
#2-A
10. FIELD OR WILDCAT NAME
Blanco Mesaverde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35, T27N, R4W NMPM
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mex.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
7003' Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-26-78: Drill 8 3/4" hole to 4105' K.B. - Ran 4093' 7" 23# K-55 LT&C Rge 3 & set @ 4105' K.B. - Cement w/150 sx 65/35 poz w/12% gel' & 100 sx Cl "B" w/2% CaCl₂ & 1/4# Celloflake/sx. WOC 12 hrs. Top cement by temp. survey - 2900'

1-27-78: Test casing to 1200 psi - O.K.

1-29-78: Air drilled 6 1/2" hole 6300' K.B.

1-30-78: Schlumberger - Ind. Gamma Ray - FDC & SNP. Ran 4 1/2" 1005# K-55 LT&C Rge 3 Liner (2319.56') - Set @ 6293'. F.C. @ 6249' - Top @ 3973' - Cemented w/275 sx 50-50 poz w/4% gel 0.4 FLA and 10# fine Gilsonite/sk. Plug down 7:45 a.m. @ 1000 psi. O.K. WO Completion Rig.

Subsurface Safety Valve: Mand. and Type Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Sr. Drlg. Engr. DATE 2-1-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 2 1978

U. S. GEOLOGICAL SURVEY
DENVER, CO. 802