

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
EL PASO NATURAL GAS CO.
3. ADDRESS OF OPERATOR
BOX 289; FARMINGTON, NEW MEXICO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1140'S, 1050'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☒
FRACTURE TREAT ☐ ☒
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

5. LEASE
SF 079365A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Rincon Unit
8. FARM OR LEASE NAME
Rincon Unit
9. WELL NO.
83A
10. FIELD OR WILDCAT NAME
Blanco MV
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 23 T-27-N R-6-W NMP
12. COUNTY OR PARISH
Rio Arriba
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6658' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/14/78: T.D. 3712'. Ran 89 joints 7", 20# K-55 intermediate casing 3700' set 3712'. Cemented with 294 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2475'

8/17/78: T.D. 6003'. Ran 59 joints 4 1/2", 10.5#, K-55 casing liner, 2451' set 3552-6003'. Float collar set at 5985'. Cemented with 472 cu. ft. cement. WOC 18 hours. Top of cement 2475'.

11/29/78: PBSD 5985'. Tested casing to 3500#, OK. Perfed C.H. 4977-82, 5002-14, 5024-36, 5054-75, 5080-87, 5090-5100', 5120-26 with 18 SPZ. Fraced w/79,000# 20/40 sand and 79,000 gallons water. Perfed Mass. P.L. 5544-56', 5573-84', 5589-5600', 5616-24-, 5834-44' 5658-74', 5697-5713', 5726-36', 5750-56 with 16 SPZ. Fraced w/90,000# 20/40 sand and 95,370 gallons wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Duise TITLE Drilling Clerk DATE 12/6/78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Perfed Lower Point Lookout 5798-5808', 5827-35', 5844-56'
5872-86', 5898-5908', 5934-50' with 16 SPZ. Fraced w/ 5000
50,000# 20/40 sand and 50,000 gallons water. Flushed
w/ 7518 gallons water.

C.B() : 1976() - 214-149