## UNITED STATES

	Budget Bureau No. 42-	R142
5. LEASE	** , , , , , , , , , , , , , , , , , ,	

	DEPARTMENT OF THE INTERIOR	SF 080668
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use th	RY NOTICES AND REPORTS ON WELLS	
1. Oil	Form 9–331–C for such proposals.)  gas X Other	8. FARM OR LEASE NAME San Juan 27-4 Unit
	OF OPERATOR	9. WELL NO. 134 (awar)
	Paso Natural Gas Company SS OF OPERATOR	TO. FIELD OR WILDCAT NAME   Blanco Mesa Verd & Blanco M
Р.	O. Box 289, Farmington, NM ON OF WELL (REPORT LOCATION CLEARLY. See space 17	II. SEC., T., R., M., OR BLK. AND SURVEY OR
below.) AT SUR	11001C 10501W	NMPM
AT TOP	P PROD. INTERVAL: AL DEPTH:	12. COUNTY OR PARISH 13. STATE  Rio Arriba New Mexico  14. API NO.
	APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
	T, OR OTHER DATA  OR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6715' GL
FRACTURE SHOOT OR REPAIR WE PULL OR A MULTIPLE ( CHANGE ZO ABANDON* (other)	ACIDIZE	1980 (NOTE: Report results of multiple completion or zone chánge on Form 9-330.)
includir	IBE PROPOSED OR COMPLETED OPERATIONS (Clearly stangestimated date of starting any proposed work. If well is	directionally drilled, give subsurface locations and
illeasui	ed and true vertical depths for all markers and zones pertine	mt to this work.)*
7 - 5 - 80:	Set a Bridge Plug at 3850'. Properfied Pictured Cliffs 3608,3615 3674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/ 6132 gal. wtr.	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668
0-5-80:	Set a Bridge Plug at 3850'. Properfed Pictured Cliffs 3608,36153674,3680' W/l SPZ. Fraced w/66,	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668 000# 10/20 sand, 76,000 gal.  J-55 tubing 6094'. set at 6104 oints of 1 1/4", 2.4#, J-55
0-5-80:	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'.	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668 000# 10/20 sand, 76,000 gal.  J-55 tubing 6094'. set at 6104 oints of 1 1/4", 2.4#, J-55
0-5-80:	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'.	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668 000# 10/20 sand, 76,000 gal.  J-55 tubing 6094'. set at 6104 oints of 1 1/4", 2.4#, J-55
0-5-80:	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'.	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668 000# 10/20 sand, 76,000 gal.  J-55 tubing 6094'. set at 6104 oints of 1 1/4", 2.4#, J-55 set at 3636'.
0-5-80: 0-7-80: Subsurface	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'. Stubing 3657' set at 3668'. S.N.	ssure tested to 3500#, OK. 5,3622,3637,3644,3650,3662,3668 000# 10/20 sand, 76,000 gal.  J-55 tubing 6094'. set at 6104 oints of 1 1/4", 2.4#, J-55 set at 3636'.
0-5-80: 0-7-80: Subsurface	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'. Stubing 3657' set at 3668'. S.N.	Set @ Ft.
0 - 5 - 80: 0 - 7 - 80: Subsurface	Set a Bridge Plug at 3850'. Preperfed Pictured Cliffs 3608,36153674,3680' W/1 SPZ. Fraced w/66, wtr. Flushed w/6132 gal. wtr.  Ran 192 joints of 2 3/8", 4.7#, S.N. set at 6074'. Ran 120'. tubing 3657' set at 3668'. S.N.	Set @ Ft.

OCT-27, 1980

FARMINGTON DISTRICT

\*See Instructions on Reverse Side