Form	9-331	
(May	1963)	

UNITED STATES

SUBMIT	IN	TRIPL	CA?	LE.
(Other 1	nstr	uctions	on	re-
verse side	:)			

Form a Budget	pprov- Bures	eđ. 10 N	o. 4	2∕R	142
DESIGN					

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

, ı	1411						
	GEO	OGI	C Δ1	SH	٦١	/FY	

MENI	OF 1	IHEI	NIERIUR	verse side)	
	-1-1	CLIE	NEV		

5.	LEASE	DESIGNATION	AND	SERIAL
	NM-C	560415		,

GEO	LOGICAL	SURVEY

S	UND	RY	NOTICES	AND	REPOR	(15	ON	W	FLL2	
se			for proposals to "APPLICATION	delli or to	deepen or	plug	back to	э а	different	reservoir.

-	7.	UNIT	AGR	EEMEN:	NAME	i	
_		FARM	OR	LEASE	NAME		 _

	WE'L		WELL	K	OTHER
-	NAME	OF OP	ERATOR		

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, NM 87401 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface

810' FSL & 1830' FEL

Companero 9. WELL NO. #2

10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde Tapacito Pictured Cliffs
11. SEC., T., B., M., OR BLE. AND
SURVEY OR AREA

Sec. 12, T27N, R4W

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NO. 7149' GR

12. COUNTY OR PARISH | 13. STATE Rio Arriba MM

16.

FRACTURE TREAT

REPAIR WELL (Other)

SHOOT OR ACIDIZE

proposed work. I nent to this work.)

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: PULL OR ALTER CASING TEST WATER SHUT-OFF MULTIPLE COMPLETE CHANGE PLANS

WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING Casing Report

REPAIRING WELL ALTERING CASING ABANDONMENT*

(Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF :

Set 105 joints (4344.19') of 7", 20#, K-55 casing at 4356.19'. 7-26-79 Cemented with 110 sacks of Class "B", 50/50 Poz with 6% gel and 1/4# flocel per sack followed by 50 sacks of Class "B" with 2% CaCl₂ and 1/4# flocel per sack. Plug down at 2:40 AM, 7-27-79.

Set 56 joints (2359.36') of 4 1/2", 10.5#, K-55, ST & C casing from 7-31-79 4179' - 6547'. Cemented with 272 sacks of Class "B", 50/50 Poz with 6% gel, 1/4# flocel per sack and .6% Halad 9. Plug down at 9:50 AM, 7-31-79.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager DATE 8-1-79

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

AUG 6 1979

The.