

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1810'S, 790'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

SF 079394

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-5 Unit

8. FARM OR LEASE NAME

San Juan 27-5 Unit

9. WELL NO.

68A

10. FIELD OR WILDCAT NAME

S. Blanco PC & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR

AREA Sec. 33, T-27-N, R-5-W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6514' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-14-80: PBTD 5785'. Tested casing to 3500#, OK. Perfed Lower & Mass. P.L. 5379, 5384, 5389, 5404, 5416, 5426, 5450, 5456, 5461, 5466, 5482, 5503, 5509, 5531, 5538, 5556, 5652, 5659, 5666, 5713, 5763' W/1 SPZ. Fraced w/ 49,000# 20/40 sand, 98,000 gal. wtr. Flushed w/ 7300 gal. wtr.

11-15-80: Perfed Cliff House & Menefee: 4844, 4850, 4855, 4904, 4910, 4916, 4927, 4932, 4937, 4942, 4949, 4957, 4962, 4975, 4981' W/1 SPZ. Fraced w/ 37,000# 20/40 sand, 78,000 gal. wtr. flushed w/ 6900 gal. wtr.

Perfed Pictured Cliffs:

3218-24; 3230-48; 3248-64' W/12 spz. Fraced w/ 40,000# 10/20 sand, 50,000 gal. wtr. Flushed w/ 5500 gal. wtr. Dropped 2 sets of 12 balls each.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED N. J. Duises TITLE Drilling Clerk DATE November 19, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

