

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1560'S, 1595'W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

5. LEASE

SF 080675

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-4 Unit

8. FARM OR LEASE NAME

San Juan 27-4 Unit

9. WELL NO.

120 (PM)

10. FIELD OR WILDCAT NAME

Tapacito PC Ext. Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34, T-27-n, R-4-W
N.M.P.M.

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7251' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-29-79: PBDT 6686'. Tested casing to 3500#, OK. Perfed Mass. & Lower P.L. 6184,6192, 6241,6245,6249,6275,6287,6292,6297,6300,6307,6314,6320,6331,6337,6344,6361, 6372,6492,6537,6549,6582,6600,6648' W/1SPZ. Fraced w/ 86,000# 20/40 sand, 172,000 gal. wtr. Flushed w/8526 gal. wtr.

12-30-79: Perfed Men. & C.H. 5747,5751,5754,5765,5770,5774,5777,5788,5791,5821,5825,5827, 5841,5845,5849,5853' W/1 SPZ. Fraced w/31,000# 20/40 sand, 62,000 gal. wtr. flushed w/8232 gal. wtr.

Perfed P.C. 4060-4086,4092-4102,4118-4140' W/12 SPZ. Fraced w/58,000# 10/20 sand, 64,920 gal. wtr. Dropped 2 sets of 12 balls each. Flushed w/6920 gal. wtr.

Subsurface Safety Valve: Manu. and Type

Set @

DIST. 3 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

N. P. Busco

TITLE

Drilling Clerk

DATE

December 31, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JAN 7 1980

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

JAN 17 1980

BY