UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 079365		
DEPARTMENT OF THE INTERIOR			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different	San Juan 28-6 Unit		
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas 🗔	San Juan 28-6 Unit		
well well other	9. WELL NO.		
2. NAME OF OPERATOR	69A		
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Blanco Mesa Verde		
P.O. Box 289, Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR		

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1460'N, 800'W	AREA Sec. 24, T-27-N, R
AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE Fio Arriba New Mexi 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	

15. ELEVATIONS (SHOW DF, KDB, AND WD) 6614' GL

AREA Sec. 24, T-27-N, R-6-W NMPM

New Mexico

REQUEST FOR APPROVAL TO:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	
PULL OR ALTER CASING [
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON*	
(other)	
	_

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

SUBSEQUENT REPORT OF:

(NOTE: Report results of multiple completion or zone change on Ferm 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-25-80: TD 3713'. Ran 84 joints 7", 20#, K-55 intermediate casing 3701' set at 3713'. Cemented w/ 223 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2800'.

TD 5968'. Ran 59 joints 4 1/2", 10.5#, K-55 casing liner 2390' set 3578-6-29-80: 5968'. Float collar set at 5950'. Cemented w/.413 cu. ft. cement. WOC 18 hours.

U. S. GEOLOGICAL SURVEY FARMINGTON, N. M.

Subsurface Safety Valve: Manu. and Type		Set @	Ft.
18. I hereby certify that the foregoing is true and correct			
18. I hereby certify that the foregoing is true and correct SIGNED TITLE	Drilling Clerk	July 2, 1980	
(This space for Fede	eral or State office use)	,	

*See Instructions on Reverse Side

JUL 1 1 1980

BY EARMINGTON DISTRICT