

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1120'S, 1800'E

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

SF-080674

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-4 Unit

8. FARM OR LEASE NAME

San Juan 27-4 Unit

9. WELL NO.

138 (PM)

10. FIELD OR WILDCAT NAME

Tapacito PC & Blanco MV

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 16, T-27-N, R-4-W NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD) 7177' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-20-80: PBSD 6667'. Tested casing to 3500#, Perfed M.V.:  
5768, 5777, 5789, 5826, 5839, 5845, 5870, 5876, 5882, 6244, 6250, 6256, 6262,  
6268, 6305, 6312, 6333, 6347, 6356, 6373, 6456, 6472, 6511, 6556' W/1 SPZ. Fraced w/  
54,500# 20/40 sand 109,000 gal. wtr. Flushed w/ 8316 gal. wtr.

Perfed Pictured Cliffs:

4058-4076', 4076-4094', 4108-4132' W/16 SPZ. Fraced w/ 50,000# 10/20 sand,  
56,300 gal. wtr. Flushed w/ 6888 gal. wtr. Dropped 2 sets of 16 balls each.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Reppa Shadford TITLE Drilling Clerk DATE Sept. 22, 1980

NAME FOR RECORD

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

BY

BW