

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1110'N, 1050'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☒
FRACTURE TREAT ☐	☐
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

5. LEASE

SF 079527

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 27-4 Unit

8. FARM OR LEASE NAME

San Juan 27-4 Unit

9. WELL NO.

35A

10. FIELD OR WILDCAT NAME

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T-27-N, R-36-W NMPM

12. COUNTY OR PARISH

13. STATE

Rio Arriba New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7254' GL

1980

(NOTE: Report results of multiple completions or change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

0-1-80: PBTD 6695'. Tested casing to 3500#, OK.
Perfed Massive & Lower Point Lookout:
6273, 6278, 6283, 6290, 6296, 6301, 6307, 6340, 6351, 6356, 6370,
6382, 6398, 6416, 6444, 6483, 6503, 6541, 6638, 6651' W/1SPZ.
Fraced w/ 158,000# 20/40 sand, 116,000 gal. wtr.
Flushed w/ 7980 gal. wtr.

Found leak on top of liner. Squeezed cement Liner top
w/354 cu. ft. cement.

0-3-80: Pressure tested did not hold. Set RTTS at 4362'. Squeezed cement
top of liner at 4240' w/ 177 cu. ft. cement.

(Continued on Back)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. B. Smith TITLE Drilling Clerk DATE October 25, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

BW

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-148

10-4-80: Perfid Cliff House & MeneFee:
5822,5835, 5874,5889,5894,5915,5920,5934,5939
6125,6130,6184,6200' W/I SPZ. Fraced w/
23,260# 20/40 sand, 38,600 gal. wtr. Flushed
w/ 8250 gal.wtr.
10-5-80: Set Bridge Plug at 4440'. Set 4 1/2" RTTS at
4270'. Pressure tested squeeze to 3500#.
Set 7" RTTS at 4044'. Cemented w/ 177
cu. ft. cement.
10-9-80: Ran 238, joints 2 3/8,4.7#, J-55 tubing 6620
set at 6630'. S.N. set at 6598'.