

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1760'S, 1540'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐


SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.



5. LEASE
SF 079391

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 27-5 Unit

8. FARM OR LEASE NAME
San Juan 27-5 Unit

9. WELL NO.
86M (MD)

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde & Basin Dak

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T-27-N, R-5-W NMPM

12. COUNTY OR PARISH | 13. STATE
R.A. | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7334' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 10-15-80: TD 4543'. Ran 111 joints 9 5/8", 40#, N-80 intermediate casing 4531' set at 4543'. Cemented w/ 695 cu. ft. cement. WOC 12 hours held 1200#/30 minutes. Top of cement at 3100'.
- 10-18-80: TD 6955'. Ran 61 joints 7", 23#, N-80 casing liner 2555' set 4400-6955'. Float collar set at 6910'. Cemented w/ 656 cu. ft. cement. WOC.
- 10-23-80: TD 8604'. Ran 49 joints 4 1/2", 10.5 & 11.6 K-55 N-80 casing liner 1762' set 6842-8604'. Float collar set at 8594'. Cemented 314 cu. cement. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. G. Guisaco TITLE Drilling Clerk DATE October 28, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

BW